

CISCO *Live!*

GO BEYOND

#CiscoLiveAPJC



Introduction to SRv6 uSID Technology

Jakub Horn
Principal Technical Marketing Engineer
BRKMPL-2203

Cisco Webex App

Questions?

Use Cisco Webex App to chat with the speaker after the session

How

- 1 Find this session in the Cisco Live Mobile App
- 2 Click “Join the Discussion”
- 3 Install the Webex App or go directly to the Webex space
- 4 Enter messages/questions in the Webex space

Webex spaces will be moderated by the speaker until November 15, 2024.




<https://ciscolive.ciscoevents.com/ciscolivebot/#BRKMPL-2203>



Agenda

- Introduction
- SRv6 uSID Dataplane
- SRv6 uSID Network Programming
- ISIS with SRv6
- BGP with SRv6
- Conclusion

Introduction




Understanding today's service creation


Limited Cross-domain Automation, Cumbersome Service Assurance



Legacy Central Office




Complex E2E Quality of Service (QoS)



End-to-end service provisioning is lengthy and complex

- Multiple network domains under different management teams
- Manual operations
- Heterogeneous underlay and overlay networks

SR-MPLS: SDN ready “Network as a Fabric” for service creation




SRv6: SDN, NfV, 5G ready

“Network as an API” for service creation



Homogenous Cross-domain Automation & Assurance




SRv6 uSID Dataplane




SRv6

- IPv6 Header
- Destination IP address
- Next header field:
 - TCP, UDP, ICMP....
 - IPv4, IPv6, L2
 - IPv4, IPv6




SRv6

- IPv6 Header
- Destination IP address
- Next header field:
 - TCP, UDP, ICMP....
 - IPv4, IPv6, L2
 - Hop by Hop, Dest. Options, Fragmentation, Authentication Header
 - ...




SRv6

- IPv6 Header
- Destination IP address
- Next header field:
 - TCP, UDP, ICMP....
 - IPv4, IPv6, L2
 - Hop by Hop, Dest. Options, Fragmentation, Authentication Header ...
- Routing header
 - 0 Source Route (deprecated)
 - 1 Nimrod (deprecated)
 - 2 Type 2 (RFC 6275)
 - 3 RPL (RFC 6554)




SRv6

- IPv6 Header
- Destination IP address
- Next header field:
 - TCP, UDP, ICMP....
 - IPv4, IPv6, L2
 - Hop by Hop, Dest. Options, Fragmentation, Authentication Header ...
- Routing header
 - 0 Source Route (deprecated)
 - 1 Nimrod (deprecated)
 - 2 Type 2 (RFC 6275)
 - 3 RPL (RFC 6554)
 - 4 SRH (RFC 8754)




SRH

- Segment Routing Header
- First segment
 - Pointer to very first SID



SRH

- Segment Routing Header
- First segment
 - Pointer to very first SID
- Segments left
 - Pointer to active SID
 - Active SID always in destination address



SID structure-locator

128 Bits Like IPv6 address but different semantics

1111:2222:3333:4444:5555:6666:7777:8888




Locator



Function

SRv6 full SID



BGP:2001:db8:0:4:eeee::

SA:2001::1 DA:2001:db8:0:1:1:: NH:RH
Type:4(SRH) NH:IPv4 SL:3 Segment List: [0]:2001:db8:0:4:eeee:: [1]:2001:db8:0:3:48:: [2]:2001:db8:0:2:1:: [3]:2001:db8:0:1:1::

SA:2001::1 DA:2001:db8:0:2:1:: NH:RH
Type:4(SRH) NH:IPv4 SL:2 Segment List: [0]:2001:db8:0:4:eeee:: [1]:2001:db8:0:3:48:: [2]:2001:db8:0:2:1:: [3]:2001:db8:0:1:1::


SA:2001::1 DA:2001:db8:0:3:48:: NH:RH
Type:4(SRH) NH:IPv4 SL:1 Segment List: [0]:2001:db8:0:4:eeee:: [1]:2001:db8:0:3:48:: [2]:2001:db8:0:2:1:: [3]:2001:db8:0:1:1::

SA:2001::1 DA:2001:db8:0:4:eeee:: NH:IPv4

SID structure

128 Bits Like IPv6 address but different semantics

1111:2222:3333:4444:5555:6666:7777:8888




SRv6 uSID format

: 0100 : =SRV6 uSID

16 bits here, but can be anything

SRV6 uSID Container



32 bits here,
but can be anything



SRV6 Encapsulation

SA:2001::1
DA:2001:db8:0:4:1:0:0:0
NH:RH

Type:4(SRH)
NH:IPv4|SL:1
Segment List:
[0]: 2001:db8:0:5:45:0:0:0
[1]: 2001:db8:0:4:1:0:0:0
[2]: 2001:db8:0:3:48:0:0:0
[3]: 2001:db8:0:2:1:0:0:0
[4]: 2001:db8:0:1:42:0:0:0

SA:7.5.4.3
DA:11.6.19.71
Port:UDP

UDP Header/Data


SRV6 uSID Encapsulation

SA:2001::1
DA:2001:db8:100:200:300:400:500::
NH:IPv4

SA:7.5.4.3
DA:11.6.19.71
Port:UDP

UDP Header/Data

SRv6 uSID F3216



BGP:2001:db8:4:eeee::



SA:2001::1
DA:2001:db8:1:2:3:e000:4:eeee
NH:IPv4

SA:2001::1
DA:2001:db8:2:3:e000:4:eeee::
NH:IPv4

SA:2001::1
DA:2001:db8:3:e000:4:eeee::
NH:IPv4

SA:2001::1
DA:2001:db8:4:eeee::
NH:IPv4

SRv6 uSID more than 6 SIDs?



100->200->300->400->500->600->700->800->900->a00->b00

Container 1 **2001 : 0db8** : 0100 : 0200 : 0300 : 0400 : 0500 : 0600

Container 2 **2001 : 0db8** : 0700 : 0800 : 0900 : 0a00 : 0b00 : 0000

SA:2001::1

~~DA:2001:db8:100:100:100:100:100~~

NH:IPv4

Type:4(SRH)

NH:IPv4| **SL:0**

Segment List:

[0]: 2001:db8:700:800:900:a00:b00::

SA:7.5.4.3

DA:11.6.19.71

Port:UDP

UDP Header/Data

Shift & Forward

END of Container

-> is there SRH?


Decrement SL

copy new SID (Container)

PSP

Sets, Global ID Block (GIB), Local ID Block (LIB)

- Within a Block, SIDs are allocated: FCBB:BB00:XXXX
- SID can be:
 - Global: shortest path to a node – globally unique
 - Local: a local function – not globally unique



SRv6 uSID configuration

segment-routing

srv6

locators

locator **MAIN**

micro-segment behavior unode **psp-usd**

prefix **fcbb:bb00:1::/48**

Name to reference


uSID

Locator Prefix


Flow label

- What for?
- Entropy encoding encap
 - 5 Tuple Hash into flow label
- Used for Hash on P routers

HASH



Flow label



SRv6 Network Programming





SRv6 functions: RFC 8986

Codename		Behavior	
End	uN	Endpoint	[Node SID]
End.X	uA	Endpoint with Layer-3 cross-connect	[Adj SID]
End.B6.Insert	uB6.Insert	Endpoint bound to an SRv6 policy	[BSID]
End.B6.Encap	uB6.Encaps	Endpoint bound to an SRv6 encapsulation policy	[BSID]
End.DX6	uDX6	Endpoint with decapsulation and IPv6 cross-connect	[L3VPN Per-CE]
End.DX4	uDX4	Endpoint with decapsulation and IPv4 cross-connect	[L3VPN Per-CE]
End.DT6	uDT6	Endpoint with decapsulation and specific IPv6 table lookup	[L3VPN Per-VRF]
End.DT4	uDT4	Endpoint with decapsulation and specific IPv4 table lookup	[L3VPN Per-VRF]
End.DX2	uDX2	Endpoint with decapsulation and L2 cross-connect	[E-LINE]
End.DT2U/M	uDT2U/M	Endpoint with decapsulation and L2 unicast lookup / flooding	[E-LAN]
End.DTM	uDTM	Endpoint with decapsulation and MPLS table lookup	[Interworking]
H.Insert / H.Encaps		Headend with Insertion / Encapsulation of / into an SRv6 policy	[TiLFA]
H. Encaps.L2		H.Encaps Applied to Received L2 Frames	[L2 Port Mode]
H.Encaps.M		H.Encaps Applied to MPLS Label Stack	[Interworking]

END- default endpoint (Node SID)

- *Decrement SL*
- *Copy active SID*
- *Forward*





• Different flavors:

- End
- End with PSP
- End with USP
- End with PSP & USP
- End with USD
- End with PSP & USD
- End with USP & USD
- End with PSP, USP & USD

- End with **NEXT**-ONLY-CSID
- End with **NEXT**-CSID
- End with **NEXT**-CSID & PSP
- End with **NEXT**-CSID & USP
- End with **NEXT**-CSID, PSP & USP
- End with **NEXT**-CSID & USD
- End with **NEXT**-CSID, PSP & USD
- End with **NEXT**-CSID, USP & USD
- End with **NEXT**-CSID, PSP, USP & USD

uN=END with next – default endpoint (Node SID)

- *Decrement SL*
- *Copy active SID*
- *Forward*




Better way:

- *Shift & forward*



uA=END.X with next – (Adjacency SID)



- *Shift & forward to SPECIFIC INTERFACE*

uDX4=END.DX4, uDX6=END.DX6, uDX2=END.DX2 Endpoint with Decapsulation and Xconnect

- *Decapsulate and forward to SPECIFIC INTERFACE*
- *Same as per CE Label Allocation*
- *Must be last function in SID list*




uDT4=END.DT4, uDT6=END.DT6

Endpoint with Decapsulation and Table Lookup

- *Decapsulate and table Lookup (VRF)*
- *Same as per VRF Label Allocation (aggregate label)*
- *Must be last function in SID list*



SRv6 uSID ISIS



ISIS for SRv6

LSP (Link State Packet):

TLVs:

Hostname: r2

Interfaces: Hu0/0/0/0 **uA:fcbb:0:2:e001::**
Structure: BL=32;NL=16;FL=16;AL=0


Hu0/0/0/1 **uA:fcbb:0:2:e002::**
Structure: BL=32;NL=16;FL=16;AL=0

Neighbors:
Lo0
r1

r3
IP addresses: fcbb:0:2::1/128
2001:12::2/64

Locator: **fcbb:0:2::/48**
uN:fcbb:0:2::
Structure: BL=32;NL=16;FL=0;AL=80

Capabilities: Algorithms
SIDs can insert
SIDs can decap
.....



ISIS LSP Example

IS-IS 1 (Level-2) Link State Database

LSPID LSP Seq Num LSP Checksum LSP Holdtime/Rcvd ATT/P/OL

r2.00-00 0x000000009 0x4f06 1145 /1200 0/0/0

Area Address: 49

NLPID: 0x8e

Hostname: r1

IPv6 Address: 2001::2

Metric: 10 MT (IPv6 Unicast) IPv6 fcbb:bb00:2::1/128

Prefix Attribute Flags: X:0 R:0 N:1 E:0 A:0

Metric: 1 MT (IPv6 Unicast) IPv6 fcbb:bb00:2::/48

Prefix Attribute Flags: X:0 R:0 N:0 E:0 A:0

MT: IPv6 Unicast 0/0/0

SRv6 Locator: MT (IPv6 Unicast) fcbb:bb00:2::/48 D:0 Metric: 0 Algorithm: 0

Prefix Attribute Flags: X:0 R:0 N:0 E:0 A:0

END SID: fcbb:bb00:2:: uN (PSP/USD)

SID Structure:

Block Length: 32, Node-ID Length: 16, Func-Length: 0, Args-Length: 0

Router Cap: 0.0.0.0 D:0 S:0

IPv6 Router ID: 2001::2

SR Algorithm:

Algorithm: 0

Algorithm: 1

SRv6: 0:0

Node Maximum SID Depth:

SRH Max SL: 3

SRH Max End Pop: 3

SRH Max T.insert: 3

SRH Max T.encaps: 4

SRH Max End D: 4

Metric: 10 MT (IPv6 Unicast) IS-Extended r1.00

Local Interface ID: 6, Remote Interface ID: 6

Interface IPv6 Address: 2001:12::2

Neighbor IPv6 Address: 2001:12::1

END.X SID: fcbb:bb00:2:e001:: B:0 S:0 P:0 uA (PSP/USD) Alg:0

SID Structure:

Block Length: 32, Node-ID Length: 16, Func-Length: 16, Args-Length: 0

Total Level-2 LSP count: 1 Local Level-2 LSP count: 0

Locator
Capabilities

END

END.X

SID Structure

SRv6 ISIS configuration

router isis 1

address-family ipv6 unicast

segment-routing srv6

locator MAIN


Name of the Locator



This will result in:


- Locator is advertised
- uN function is advertised
- uA for each ISIS interface is allocated and advertised

SRv6 uSID BGP




BGP

- No changes required!



L3 VPN Dataplane



SRv6 L3 VPN configuration

```
router bgp 1
 address-family vpnv4 unicast
 vrf BestEffort
  rd 1:1
  address-family ipv4 unicast
  segment-routing srv6
  locator MAIN
  alloc mode per-vrf
```

Name of the Locator



Single DT function is allocated per VRF and AF



This will result in:

- uDT4 function is allocated
- All prefixes are advertised with uDT4 function

EVPN

- No changes required!

EVPN :EVI 7543
NH:2001::3
RD-1:1
RT -1:1
uDX2- fcbb:bb00:3:e002::

iBGP

2001::1

2001::3

EVI 7543

1

IPv6 Locator - fcbb:bb00:3::/48

3


EVI 7543

uDX2 - fcbb:bb00:3:e002::

EVPN Dataplane

SA:2001::1
DA:fcbb:bb00:3:e002::
NH:L2

L2 Frame



SRv6 L2 VPWS

```
interface TenGigE0/0/0/0.7543 l2transport
encapsulation dot1q 7543
rewrite ingress tag pop 1 symmetric
```

```
l2vpn
xconnect group P2P
p2p 13-14
interface TenGigE0/0/0/0.7543
neighbor evpn evi 7543 service 7543 segment-routing srv6
```


```
evpn
evi 7543 segment-routing srv6
locator MAIN
segment-routing srv6
!
```

Name of the Locator

This will result in:

- uDX2 function is allocated per EVI
- EVI is advertised with uDX2 function

Conclusion



Conclusion

- SRv6 is fully ready for brownfield deployments
- SRv6 uSID is the only reasonable format
- SRv6 uSID supported across cisco platform
- SRv6 uSID supported across vendors

Keynote Deep Dives

Wednesday
10:30am – 11:30am



Experiences Amplified:
How AI Can Fuel
Better Employee
and Customer
Experiences

Level 1
Room 106



Smart, Secure,
Seamless:
Transforming
Experiences with
Next-Generation
Networking

Level 2
Room 204



Harness a Bold
New Era:
Transform Data
Centre and
Service Provider
Connectivity

Level 2
Room 203



Securing User to
Application and
Everything in
Between

Level 2
Melbourne Room 2



Unlocking
Digital Resilience
through Unified
Observability

The HUB
Centre Stage

Complete Your Session Evaluations



Complete a minimum of 4 session surveys and the Overall Event Survey to claim a **Cisco Live T-Shirt**.



Complete your surveys in the **Cisco Live mobile app**.



Continue your education

- Visit the Cisco Stand for related demos
- Book your one-on-one Meet the Expert meeting
- Attend the interactive education with DevNet, Capture the Flag, and Walk-in Labs
- Visit the On-Demand Library for more sessions at www.CiscoLive.com/on-demand



Thank you

CISCO *Live!*

#CiscoLiveAPJC

CISCO *Live!*

GO BEYOND

#CiscoLiveAPJC