cisco Live!

GO BEYOND

#CiscoLiveAPJC

Programmability Skills for Engineers Who Don't Want to Code

Hank Preston, Principal Engineer Learning and Certifications
ccie 38336 | devnet expert 20220001
BRKOPS-1237

Cisco Webex App

https://ciscolive.ciscoevents.com/ciscolivebot/#BRKOPS-1237

Questions?

Use Cisco Webex App to chat with the speaker after the session

How

1. Find this session in the Cisco Live Mobile App
2. Click “Join the Discussion”
3. Install the Webex App or go directly to the Webex space
4. Enter messages/questions in the Webex space

Webex spaces will be moderated by the speaker until November 15, 2024.



cisco Live!

© 2024 Cisco and/or its affiliates. All rights reserved. Cisco Public

© 2024 Cisco and/or its affiliates. All rights reserved. Cisco Public

Agenda

- Spreadsheet driven automation
- Aw CRUD, we gotta talk a little about APIs
- Source of Truth, it doesn't have to be you anymore
- pyATS - How to no-code and automate networks
- Ansible the Hammer of Network Automation

© 2024 Cisco and/or its affiliates. All rights reserved. Cisco Public

Spreadsheet Driven Automation



cisco Live!

Story Time with Hank

cisco Live!

© 2024 Cisco and/or its affiliates. All rights reserved. Cisco Public

“Network engineering runs on spreadsheets”

	A	B	C	D	E	F	G	H	I	J
1	VPN Name	Side 1 Outside	Side 1 Public IP	Side 1 Inside	Side 1 Mask	Side 2 Outside	Side 2 Public IP	Side 2 Inside	Side 2 Mask	Preshared Key
2	VPN_101	GigabitEthernet0/1	203.0.113.101	10.98.128.0	0.0.3.255	GigabitEthernet1/1	198.51.100.33	172.28.11.0	0.0.0.255	ZA788I
3	VPN_102	GigabitEthernet0/1	203.0.113.102	10.98.128.0	0.0.3.255	GigabitEthernet1/1	198.51.100.34	172.28.12.0	0.0.0.255	AM285I
4	VPN_103	GigabitEthernet0/1	203.0.113.103	10.98.128.0	0.0.3.255	GigabitEthernet1/1	198.51.100.35	172.28.13.0	0.0.0.255	LG478H
5	VPN_104	GigabitEthernet0/1	203.0.113.104	10.98.128.0	0.0.3.255	GigabitEthernet1/1	198.51.100.36	172.28.14.0	0.0.0.255	WQ378E
6	VPN_105	GigabitEthernet0/1	203.0.113.105	10.98.128.0	0.0.3.255	GigabitEthernet1/1	198.51.100.37	172.28.15.0	0.0.0.255	IQ414K
7	VPN_106	GigabitEthernet0/1	203.0.113.106	10.98.128.0	0.0.3.255	GigabitEthernet1/1	198.51.100.38	172.28.16.0	0.0.0.255	SX892U
8	VPN_107	GigabitEthernet0/1	203.0.113.107	10.98.128.0	0.0.3.255	GigabitEthernet1/1	198.51.100.39	172.28.17.0	0.0.0.255	MU655D
9	VPN_108	GigabitEthernet0/1	203.0.113.108	10.98.128.0	0.0.3.255	GigabitEthernet1/1	198.51.100.40	172.28.18.0	0.0.0.255	BE798D
10	VPN_109	GigabitEthernet0/1	203.0.113.109	10.98.128.0	0.0.3.255	GigabitEthernet1/1	198.51.100.41	172.28.19.0	0.0.0.255	ZV856J
11	VPN_110	GigabitEthernet0/1	203.0.113.110	10.98.128.0	0.0.3.255	GigabitEthernet1/1	198.51.100.42	172.28.20.0	0.0.0.255	NZ326F
12	VPN_111	GigabitEthernet0/1	203.0.113.111	10.98.128.0	0.0.3.255	GigabitEthernet1/1	198.51.100.43	172.28.21.0	0.0.0.255	JI492F
13	VPN_112	GigabitEthernet0/1	203.0.113.112	10.98.128.0	0.0.3.255	GigabitEthernet1/1	198.51.100.44	172.28.22.0	0.0.0.255	OX357R
14	VPN_113	GigabitEthernet0/1	203.0.113.113	10.98.128.0	0.0.3.255	GigabitEthernet1/1	198.51.100.45	172.28.23.0	0.0.0.255	HN203X
15	VPN_114	GigabitEthernet0/1	203.0.113.114	10.98.128.0	0.0.3.255	GigabitEthernet1/1	198.51.100.46	172.28.24.0	0.0.0.255	TM449R
16	VPN_115	GigabitEthernet0/1	203.0.113.115	10.98.128.0	0.0.3.255	GigabitEthernet1/1	198.51.100.47	172.28.25.0	0.0.0.255	HS131D
17	VPN_116	GigabitEthernet0/1	203.0.113.116	10.98.128.0	0.0.3.255	GigabitEthernet1/1	198.51.100.48	172.28.26.0	0.0.0.255	ZK468M
18	VPN_117	GigabitEthernet0/1	203.0.113.117	10.98.128.0	0.0.3.255	GigabitEthernet1/1	198.51.100.49	172.28.27.0	0.0.0.255	KO827T
19	VPN_118	GigabitEthernet0/1	203.0.113.118	10.98.128.0	0.0.3.255	GigabitEthernet1/1	198.51.100.50	172.28.28.0	0.0.0.255	XH308M
20	VPN_119	GigabitEthernet0/1	203.0.113.119	10.98.128.0	0.0.3.255	GigabitEthernet1/1	198.51.100.51	172.28.29.0	0.0.0.255	BX371N
21	VPN_120	GigabitEthernet0/1	203.0.113.120	10.98.128.0	0.0.3.255	GigabitEthernet1/1	198.51.100.52	172.28.30.0	0.0.0.255	EQ345W
22	VPN_121	GigabitEthernet0/1	203.0.113.121	10.98.128.0	0.0.3.255	GigabitEthernet1/1	198.51.100.53	172.28.31.0	0.0.0.255	CU286E
23	VPN_122	GigabitEthernet0/1	203.0.113.122	10.98.128.0	0.0.3.255	GigabitEthernet1/1	198.51.100.54	172.28.32.0	0.0.0.255	JD396Z
24	VPN_123	GigabitEthernet0/1	203.0.113.123	10.98.128.0	0.0.3.255	GigabitEthernet1/1	198.51.100.55	172.28.33.0	0.0.0.255	VQ393Y
25	VPN_124	GigabitEthernet0/1	203.0.113.124	10.98.128.0	0.0.3.255	GigabitEthernet1/1	198.51.100.56	172.28.34.0	0.0.0.255	VW636O
26	VPN_125	GigabitEthernet0/1	203.0.113.125	10.98.128.0	0.0.3.255	GigabitEthernet1/1	198.51.100.57	172.28.35.0	0.0.0.255	PW939V
27	VPN_126	GigabitEthernet0/1	203.0.113.126	10.98.128.0	0.0.3.255	GigabitEthernet1/1	198.51.100.58	172.28.36.0	0.0.0.255	UR382C
28	VPN_127	GigabitEthernet0/1	203.0.113.127	10.98.128.0	0.0.3.255	GigabitEthernet1/1	198.51.100.59	172.28.37.0	0.0.0.255	AJ178G
29	VPN_128	GigabitEthernet0/1	203.0.113.128	10.98.128.0	0.0.3.255	GigabitEthernet1/1	198.51.100.60	172.28.38.0	0.0.0.255	PH438E
30	VPN_129	GigabitEthernet0/1	203.0.113.129	10.98.128.0	0.0.3.255	GigabitEthernet1/1	198.51.100.61	172.28.39.0	0.0.0.255	OP507L
31	VPN_130	GigabitEthernet0/1	203.0.113.130	10.98.128.0	0.0.3.255	GigabitEthernet1/1	198.51.100.62	172.28.40.0	0.0.0.255	DP586R

© 2024 Cisco and/or its affiliates. All rights reserved. Cisco Public

Device configuration standard

```
crypto isakmp policy 10
  encryption aes
  hash sha256
  authentication pre-share
  group 14

crypto ipsec transform-set <TRANS_SET> esp-aes esp-sha256-hmac

crypto isakmp key <PRESHARED_KEY> address <PEER_ADDRESS>

access-list <ACL_NUM> permit ip <LOCAL_NET> <LOCAL_MASK> <REMOTE_NET> <REMOTE_MASK>

crypto map <MAP_NAME> 10 ipsec-isakmp
  set peer <PEER_ADDRESS>
  set transform-set <TRANS_SET>
  match address <ACL_NUM>

interface <OUTSIDE_INT>
  crypto map <MAP_NAME>
```


© 2024 Cisco and/or its affiliates. All rights reserved. Cisco Public

Creating the access list configuration

VPN Name	Side 1 Outside	Side 1 Public IP	Side 1 Inside	Side 1 Mask	Side 2 Outside	Side 2 Public IP	Side 2 Inside	Side 2 Mask
VPN_101	GigabitEthernet0/1	203.0.113.101	10.98.128.0	0.0.3.255	GigabitEthernet1/1	198.51.100.33	172.28.11.0	0.0.0.255



```
! Site 1 Access List
access-list <ACL_NUM> permit ip <LOCAL_NET> <LOCAL_MASK> <REMOTE_NET> <REMOTE_MASK>
```

```
! Site 1 Access List
access-list 100 permit ip 10.98.128.0 0.0.3.255 172.28.11.0 0.0.0.255
```


© 2024 Cisco and/or its affiliates. All rights reserved. Cisco Public

Creating the access list configuration

VPN Name	Side 1 Outside	Side 1 Public IP	Side 1 Inside	Side 1 Mask	Side 2 Outside	Side 2 Public IP	Side 2 Inside	Side 2 Mask
VPN_101	GigabitEthernet0/1	203.0.113.101	10.98.128.0	0.0.3.255	GigabitEthernet1/1	198.51.100.33	172.28.11.0	0.0.0.255



```
! Site 2 Access List
access-list <ACL_NUM> permit ip <LOCAL_NET> <LOCAL_MASK> <REMOTE_NET> <REMOTE_MASK>
```

```
! Site 2 Access List
access-list 100 permit ip 172.28.11.0 0.0.0.255 10.98.128.0 0.0.3.255
```


© 2024 Cisco and/or its affiliates. All rights reserved. Cisco Public

Using CONCAT function in Excel to create strings

VPN Name	Side 1 Outside	Side 1 Public IP	Side 1 Inside	Side 1 Mask	Side 2 Outside	Side 2 Public IP	Side 2 Inside	Side 2 Mask
VPN_101	GigabitEthernet0/1	203.0.113.101	10.98.128.0	0.0.3.255	GigabitEthernet1/1	198.51.100.33	172.28.11.0	0.0.0.255

```
=CONCAT("access-list 100 permit ip ",
      VPNs[@[Side 1 Inside]]," ", VPNs[@[Side 1 Mask]], " ",
      VPNs[@[Side 2 Inside]]," ", VPNs[@[Side 2 Mask]])
```

fx CONCAT

Concatenates a list or range of text strings.

Syntax

CONCAT(text1,...)

- **Text1**: text1,text2,... are 1 to 254 text strings or ranges to be joined to a single text string.

- Fill in the blank configuration creation
- Once formulas created, ”fill down” for other rows / sites

Help info on CONCAT Function

© 2024 Cisco and/or its affiliates. All rights reserved. Cisco Public

CONCAT your CONCATs for full configs

Common Config Elements

Config Type	Identification Detail	Configuration
IOS isakmp policy	10	crypto isakmp policy 10 encryption aes hash sha256 authentication pre-share group 14
IOS Transform ipsec transform	vpn_transform	crypto ipsec transform-set vpn_transform esp-aes esp-sha256-hmac

```
=CONCAT('Common Info'!$C$2,
        'Common Info'!$C$3,
        B2, D2, C2, E2)
```

Per VPN Configurations

VPN Name	Site 1 Access List	Site 1 Crypto Map	Site 1 Key	Site 1 Interface	Site 1 Full Config
VPN_101	access-list 100 permit ip 10.98.128.0 0.0.3.255 172.28.11.0 0.0.0.255	crypto map VPN_101 10 ipsec-isakmp set peer 198.51.100.33 set transform-setvpn_transform match address 100	crypto isakmp key ZA788I address 198.51.100.33	interface GigabitEthernet0/1 crypto map VPN_101	crypto isakmp policy 10 encryption aes hash sha256 authentication pre-share group 14 crypto ipsec transform-set vpn_transform esp-aes esp-sha256-hmac access-list 100 permit ip 10.98.128.0 0.0.3.255 172.28.11.0 0.0.0.255 crypto isakmp key ZA788I address 198.51.100.33 crypto map VPN_101 10 ipsec-isakmp set peer 198.51.100.33 set transform-setvpn_transform match address 100 interface GigabitEthernet0/1 crypto map VPN_101

Tip! Don’t forget to add spaces and new lines where needed

© 2024 Cisco and/or its affiliates. All rights reserved. Cisco Public

Demo!

Other Useful Functions

- MID – pull characters out of a string
- REPLACE – change characters in a string
- FIND – locate a character in a string
- TRIM – remove white space
- RAND / RANDBETWEEN – provide a random number
- Lots more!

© 2024 Cisco and/or its affiliates. All rights reserved. Cisco Public

Why Should I Care?

- Business runs on spreadsheets… not just networking
- Formulas are WAY faster and consistent than manual
  - Double check, then triple check results!
- But be careful you don’t go too far…

© 2024 Cisco and/or its affiliates. All rights reserved. Cisco Public

Aw CRUD, We Gotta Talk a Little About APIs



cisco Live!

In the Beginning… Humans Were the Only Users

© 2024 Cisco and/or its affiliates. All rights reserved. Cisco Public

In the Beginning… Humans Were the Only Users

Software displays results in User Interface (UI)

User asks for data or takes action by interacting with UI

© 2024 Cisco and/or its affiliates. All rights reserved. Cisco Public

“It’s a way for two pieces of software to talk to each other”

What exactly IS an API?

© 2024 Cisco and/or its affiliates. All rights reserved. Cisco Public

Now Software Talks to Software



© 2024 Cisco and/or its affiliates. All rights reserved. Cisco Public

APIs Aren't Scary... You Already Use Them



cisco Live!

Command line interface (CLI)

Designed for Humans... so more a UI than API

but...

- Network Management Systems
- Expect Scripts
- Paramiko/Netmiko
- NAPALM

```
#!/usr/bin/expect -f

send "conf t\n"
expect "(config)#"

send ”hostname my_switch\n"
expect "(config)#"
send "ntp server 10.10.10.101\n"
expect "(config)#"
send "ip domain-name domain.intra\n"
expect "(config)#"

send "end\n"
expect "#"
send "write mem\n"
expect "#"
```


© 2024 Cisco and/or its affiliates. All rights reserved. Cisco Public

Simple Network Management Protocol (SNMP)

"designed as a programmatic interface between management applications and devices"



https://tools.ietf.org/html/rfc3535

© 2024 Cisco and/or its affiliates. All rights reserved. Cisco Public

Representational state transfer (REST)

- API framework for simple web services
- Another use for the HTTP protocol
- Popular due to performance, scale, simplicity, and reliability

© 2024 Cisco and/or its affiliates. All rights reserved. Cisco Public

RESTCONF



© 2024 Cisco and/or its affiliates. All rights reserved. Cisco Public

The URI: what are you requesting?

https://router-01.example.com/restconf/data/Cisco-IOS-XE-native:native/hostname



- Server or Host
  - Resolves to the IP and port to connect to
- Resource
  - The location of the data or object of interest on the server

Response

```
{"Cisco-IOS-XE-native:hostname":
      "csr1000v-1"}
```

- JSON data returned
- Based on YANG model

© 2024 Cisco and/or its affiliates. All rights reserved. Cisco Public

HTTP methods: what to do?

HTTP Verb	Typical Purpose (CRUD)	Description
POST	Create	Used to create a new object, or resource. *Example: Add new book to library*
GET	Read	Retrieve resource details from the system. *Example: Get list of books from the library*
PUT	Update	Typically used to replace or update a resource. Can be used to modify or create. *Example: Update the borrower details for a book*
DELETE	Delete	Remove a resource from the system. *Example: Delete a book from the library.*

© 2024 Cisco and/or its affiliates. All rights reserved. Cisco Public

Demo!

Why should I care?

- IT system integrations
- Understand and work with automation peers
- Evaluate APIs from your products and vendors
- APIs are cool, add it to your resume!

© 2024 Cisco and/or its affiliates. All rights reserved. Cisco Public

Resources

Cisco U.

[Understanding Network Automation Essentials Learning Path]

- [Introduction to APIs]
- [NETCONF and RESTCONF]

© 2024 Cisco and/or its affiliates. All rights reserved. Cisco Public

Source of Truth, It Doesn't Have To Be You Anymore



cisco Live!

How Does Automation Work?



© 2024 Cisco and/or its affiliates. All rights reserved. Cisco Public

How Does ~~Automation~~ *Network Engineering* Work?



© 2024 Cisco and/or its affiliates. All rights reserved. Cisco Public

What types of data make up “desired state”

- IP Addresses
- Interface settings
- VLANs
- Software Versions
- Credentials
- Serial / Asset Numbers
- Neighbors
- Cables / Circuits
- Management Access
- Status
- Standards
- Application / Service Details
- Host Details

© 2024 Cisco and/or its affiliates. All rights reserved. Cisco Public

Where is the Data Found?

- In your head
- In someone else's head
- On a spreadsheet
- On a network diagram
- Text docs and notes apps
- Paper notes and scrap paper
- Within the network

© 2024 Cisco and/or its affiliates. All rights reserved. Cisco Public

Electric Wire Nuts
L Brackets
Finishing Nails
General Nails
White Nails
Large Nails
Misc. Washers
#6-32 1/2" Bolt
#6-32 1" Bolt
#6-32 1-1/2" Bolts
#8-32 3/4" Bolt
#8-32 1-1/2" Bolt
#12-24 3/4" Bolt
#12-24 1-1/2"Bolt
#12-24 2-1/2" Bolt
Pocket Screw 1" Coarse
Pocket Screw 1-1/4" Coarse
Pocket Screw 1-1/2" Coarse
Pocket Screw 2" Coarse
Pocket Screw 2" Coarse
Pocket Screw 2-1/2" Coarse
1-3/4" TapCon
2-3/4" TapCon
#6 1/2" Screw
#8 3/4" Screw
#8 1" Screw
#8 1-1/4" Screw
#8 2" Screw
#8 2 1/2" Screw
2-1/2" General Screws
3" General Screws
1-1/4" General Screws
1-5/8" General Screws
1-5/8" General Screws
Small Misc. Screws
Misc. Nuts
2-1/2" General Screws
1" General Screws
Medium Misc. Screws

BRKOPS-1237

Device installation workflow with source of truth



© 2024 Cisco and/or its affiliates. All rights reserved. Cisco Public

Common Automation Source of Truth Options

- CSV Files
- YAML / JSON Files
- Git Repositories
- APIs into Other Applications
  - IPAM / DCIM
  - Secret Management
  - Service Desk / CDB

© 2024 Cisco and/or its affiliates. All rights reserved. Cisco Public

“Single” Source of Truth Realities

- “Single” is a fantasy
- Goal should be ”single per domain”
  - IPAM, DCIM, Secrets, etc.
- It takes discipline to maintain
- Culture change – “Document First”
- Go in phases and celebrate success

© 2024 Cisco and/or its affiliates. All rights reserved. Cisco Public

pyATS – How to No-code and Automate Networks



cisco Live!

“Could you get me this info from all of the devices in the network?”



“Could you get me this info from all of the devices in the network?”

- Serial numbers
- Interface status
- Routing table
- ARP / MAC tables
- Logs
- Etc.
- Etc.
- Etc.

© 2024 Cisco and/or its affiliates. All rights reserved. Cisco Public

developer@sandbox-iosxe-latest-1.cisco.com (ssh)

```
      & - replicated local route overrides by connected

Gateway of last resort is 10.10.20.254 to network 0.0.0.0

S*    0.0.0.0/0 [1/0] via 10.10.20.254, GigabitEthernet1
      10.0.0.0/8 is variably subnetted, 3 subnets, 2 masks
C        10.0.0.10/32 is directly connected, Loopback10
C        10.10.20.0/24 is directly connected, GigabitEthernet1
L        10.10.20.48/32 is directly connected, GigabitEthernet1
csr1000v-1#show ip int bri
Interface              IP-Address      OK? Method Status                Protocol
GigabitEthernet1       10.10.20.48     YES NVRAM  up                    up
GigabitEthernet2       unassigned      YES NVRAM  administratively down down
GigabitEthernet3       unassigned      YES NVRAM  administratively down down
Loopback10             10.0.0.10       YES other  up                    up
csr1000v-1#
```

developer@sandbox-iosxe-latest-1.cisco.com (ssh)

```
      & - replicated local route overrides by connected

Gateway of last resort is 10.10.20.254 to network 0.0.0.0

S*    0.0.0.0/0 [1/0] via 10.10.20.254, GigabitEthernet1
      10.0.0.0/8 is variably subnetted, 3 subnets, 2 masks
C        10.0.0.10/32 is directly connected, Loopback10
C        10.10.20.0/24 is directly connected, GigabitEthernet1
L        10.10.20.48/32 is directly connected, GigabitEthernet1
csr1000v-1#show ip int bri
Interface              IP-Address      OK? Method Status                Protocol
GigabitEthernet1       10.10.20.48     YES NVRAM  up                    up
GigabitEthernet2       unassigned      YES NVRAM  administratively down down
GigabitEthernet3       unassigned      YES NVRAM  administratively down down
Loopback10             10.0.0.10       YES other  up                    up
csr1000v-1#
```

developer@sandbox-iosxe-latest-1.cisco.com (ssh)

```
Gateway of last resort is 10.10.20.254 to network 0.0.0.0

S*    0.0.0.0/0 [1/0] via 10.10.20.254, GigabitEthernet1
      10.0.0.0/8 is variably subnetted, 3 subnets, 2 masks
C        10.0.0.10/32 is directly connected, Loopback10
C        10.10.20.0/24 is directly connected, GigabitEthernet1
L        10.10.20.48/32 is directly connected, GigabitEthernet1
csr1000v-1#show ip int bri
Interface              IP-Address      OK? Method Status                Protocol
GigabitEthernet1       10.10.20.48     YES NVRAM  up                    up
GigabitEthernet2       unassigned      YES NVRAM  administratively down down
GigabitEthernet3       unassigned      YES NVRAM  administratively down down
Loopback10             10.0.0.10       YES other  up                    up
csr1000v-1#
```

We all have our cheats...

developer@sandbox-iosxe-latest-1.cisco.com (ssh)

```
      & - replicated local route overrides by connected

Gateway of last resort is 10.10.20.254 to network 0.0.0.0

S*    0.0.0.0/0 [1/0] via 10.10.20.254, GigabitEthernet1
      10.0.0.0/8 is variably subnetted, 3 subnets, 2 masks
C        10.0.0.10/32 is directly connected, Loopback10
C        10.10.20.0/24 is directly connected, GigabitEthernet1
L        10.10.20.48/32 is directly connected, GigabitEthernet1
csr1000v-1#show ip int bri
Interface              IP-Address      OK? Method Status                Protocol
GigabitEthernet1       10.10.20.48     YES NVRAM  up                    up
```

developer@sandbox-iosxe-latest-1.cisco.com (ssh)

```
      & - replicated local route overrides by connected

Gateway of last resort is 10.10.20.254 to network 0.0.0.0

S*    0.0.0.0/0 [1/0] via 10.10.20.254, GigabitEthernet1
      10.0.0.0/8 is variably subnetted, 3 subnets, 2 masks
C        10.0.0.10/32 is directly connected, Loopback10
C        10.10.20.0/24 is directly connected, GigabitEthernet1
L        10.10.20.48/32 is directly connected, GigabitEthernet1
csr1000v-1#show ip int bri
Interface              IP-Address      OK? Method Status                Protocol
GigabitEthernet1       10.10.20.48     YES NVRAM  up                    up
```


© 2024 Cisco and/or its affiliates. All rights reserved. Cisco Public

Per device results

Command to Run

```
pyats parse "show ip route" \
   --testbed-file testbed.yaml \
   --output output/ip_routes
```

Captured Output

Network Inventory

Per Device Results
- Parse = JSON Data
- Console = Raw Data

```
100%| ████████████████████████████████████ | 1/1 [00:00<00:00, 1.89it/s]
+==============================================================================+
| Genie Parse Summary for rtr1 |
+==============================================================================+
| Connected to rtr1 |
| - Log: output/ip_routes/connection_rtr1.txt |
|------------------------------------------------------------------------------|
| Parsed command 'show ip route' |
| - Parsed structure: output/ip_routes/rtr1_show-ip-route_parsed.txt |
| - Device Console: output/ip_routes/rtr1_show-ip-route_console.txt |
|------------------------------------------------------------------------------|

100%| ████████████████████████████████████ | 1/1 [00:00<00:00, 2.00it/s]
+==============================================================================+
| Genie Parse Summary for rtr2 |
+==============================================================================+
| Connected to rtr2 |
| - Log: output/ip_routes/connection_rtr2.txt |
|------------------------------------------------------------------------------|
| Parsed command 'show ip route' |
| - Parsed structure: output/ip_routes/rtr2_show-ip-route_parsed.txt |
| - Device Console: output/ip_routes/rtr2_show-ip-route_console.txt |
|------------------------------------------------------------------------------|

100%|████████████████████████████████████| 1/1 [00:00<00:00, 2.05it/s]
+==============================================================================+
| Genie Parse Summary for rtr3 |
+==============================================================================+
| Connected to rtr3 |
| - Log: output/ip_routes/connection_rtr3.txt |
|------------------------------------------------------------------------------|
| Parsed command 'show ip route' |
| - Parsed structure: output/ip_routes/rtr3_show-ip-route_parsed.txt |
| - Device Console: output/ip_routes/rtr3_show-ip-route_console.txt |
|------------------------------------------------------------------------------|
```


© 2024 Cisco and/or its affiliates. All rights reserved. Cisco Public

Demo

pyATS Can Do Much More

- Collect network baselines
- Quickly find differences
- Create robust network tests (does require coding)

© 2024 Cisco and/or its affiliates. All rights reserved. Cisco Public

Resources

Cisco U.

- Network Automation Testing with pyATS
- Test-Driven Automation with Cisco pyATS Using SSH
- pyATS home on DevNet
- pyATS CLI Hands On Lab

© 2024 Cisco and/or its affiliates. All rights reserved. Cisco Public

Ansible – The Hammer of Network Automation

cisco Live!

Why Ansible?

- OpenSource infrastructure as code tool
- Low barrier of entry into automation
- Coding skills not needed
- Very popular -> lots of examples
- Broad network automation use cases

© 2024 Cisco and/or its affiliates. All rights reserved. Cisco Public

Ansible, It Isn't "Code"... It's Just YAML 🙂

```
- name: Side 2 Config
  loop: "{{ vpns.list }}"
  loop_control:
    label: "{{ item.vpn_name }} Side 2"

  vars:
    vpn_name: "{{ item.vpn_name }}"
    preshared_key: "{{ item.preshared_key }} "
    source_network: "{{ item.side_2_inside }}"
    source_mask: "{{ item.side_2_mask }} "
    destination_network: "{{ item.side_1_inside }}"
    destination_mask: "{{ item.side_1_mask }}"
    tunnel_destination: "{{ item.side_1_public_ip }}"
    tunnel_interface: "{{ item.side_2_outside }} "

  ansible.builtin.template:
    src: ios-vpn.j2
    dest: configs/{{ item.vpn_name }}-side2-config.txt
```


© 2024 Cisco and/or its affiliates. All rights reserved. Cisco Public

Another approach to the spreadsheet driven automation

Maybe I’m ready to try something new…

© 2024 Cisco and/or its affiliates. All rights reserved. Cisco Public

```
vpn_name,side_1_outside,      side_1_public_ip,side_1_inside,
VPN_101, GigabitEthernet0/1,203.0.113.101,    10.98.128.0,
VPN_102, GigabitEthernet0/1,203.0.113.102,    10.98.128.0,
VPN_103, GigabitEthernet0/1,203.0.113.103,    10.98.128.0,
VPN_104, GigabitEthernet0/1,203.0.113.104,    10.98.128.0,
VPN_105, GigabitEthernet0/1,203.0.113.105,    10.98.128.0,
VPN_106, GigabitEthernet0/1,203.0.113.106,    10.98.128.0,
VPN_107, GigabitEthernet0/1,203.0.113.107,    10.98.128.0,
VPN_108, GigabitEthernet0/1,203.0.113.108,    10.98.128.0,
VPN_109, GigabitEthernet0/1,203.0.113.109,    10.98.128.0,
```

CSV

Jinja

```
crypto isakmp key {{ preshared_key }} address

crypto map {{ vpn_name }} 10 ipsec-isakmp
 set peer {{ tunnel_destination }}
 set transform-setvpn_transform
 match address 100

interface {{ tunnel_interface }}
 crypto map {{ vpn_name }}
```

```
- name: Create VPN Configurations From CSV File
  hosts: localhost
  gather_facts: false

  tasks:
  - name: Read VPN List from CSV file
    community.general.read_csv:
      path: vpn_list.csv
    register: vpns

  - name: Side 2 Config
    loop: "{{ vpns.list }}"
    loop_control:
      label: "{{ item.vpn_name }} Side 2"
    vars:
      vpn_name: "{{ item.vpn_name }}"
      preshared_key: "{{ item.preshared_key }} "
      source_network: "{{ item.side_2_inside }}"
      source_mask: "{{ item.side_2_mask }} "
      destination_network: "{{ item.side_1_inside }}"
      destination_mask: "{{ item.side_1_mask }}"
      tunnel_destination: "{{ item.side_1_public_ip }}"
      tunnel_interface: "{{ item.side_2_outside }} "
    ansible.builtin.template:
      src: ios-vpn.j2
      dest: configs/{{ item.vpn_name }}-side2-config.txt
```

ANSIBLE

CLI

```
crypto isakmp policy 10
 encryption aes
 hash sha256
 authentication pre-share
 group 14

crypto ipsec transform-set vpn_transform esp-aes esp-sha256-hmac

access-list 100 permit ip 172.28.14.0 0.0.0.255 10.98.128.0 0.0.3.255

crypto isakmp key WQ378E address 203.0.113.104

crypto map VPN_104 10 ipsec-isakmp
 set peer 203.0.113.104
 set transform-setvpn_transform
 match address 100

interface GigabitEthernet1/1
 crypto map VPN_104
```


© 2024 Cisco and/or its affiliates. All rights reserved. Cisco Public

Demo!

Ansible Can Do Much More

- Apply configurations directly to devices
- Complex workflows
- Manage network, compute, storage, cloud, etc. at once

© 2024 Cisco and/or its affiliates. All rights reserved. Cisco Public

Resources
(Training)

Cisco U.

- Network Automation with Ansible
- An Introduction to Ansible Roles
- Configuring IOS XE with Ansible
- Demo Example Code

cisco Live!

© 2024 Cisco and/or its affiliates. All rights reserved. Cisco Public

Resources
(Documentation)

- Ansible on DevNet
- Ansible Core Docs
  - Reading from CSV
  - Using Jinja Templates
- Jinja Template Documentation

© 2024 Cisco and/or its affiliates. All rights reserved. Cisco Public

BONUS...
What About AI?



cisco Live!

You 3:48 PM

Using the data from the below CSV data,

```
vpn_name,tunnel_interface,side_1_public_ip,source_network,source_mask,side_2_outside,tunnel_destination,destination_network,desti
VPN_101,GigabitEthernet0/1,203.0.113.101,10.98.128.0,0.0.3.255,GigabitEthernet1/1,198.51.100.33,172.28.11.0,0.0.0.255,ZA788I
VPN_102,GigabitEthernet0/1,203.0.113.102,10.98.128.0,0.0.3.255,GigabitEthernet1/1,198.51.100.34,172.28.12.0,0.0.0.255,AM285I
```

generate a configuration from each row based on the below jinja2 template

```
! VPN {{ vpn_name }}
crypto isakmp policy 10
 encryption aes
 hash sha256
 authentication pre-share
 group 14

crypto ipsec transform-set vpn_transform esp-aes esp-sha256-hmac

access-list 100 permit ip {{ source_network }} {{ source_mask }} {{ destination_network }} {{ destination_mask }}

crypto isakmp key {{ preshared_key }} address {{ tunnel_destination }}

crypto map {{ vpn_name }} 10 ipsec-isakmp
 set peer {{ tunnel_destination }}
 set transform-setvpn_transform
 match address 100

interface {{ tunnel_interface }}
 crypto map {{ vpn_name }}
```


© 2024 Cisco and/or its affiliates. All rights reserved. Cisco Public

BridgeIT - Enterprise Chat AI 3:48 PM

Based on the provided Jinja2 template and the CSV data, here are the generated configurations for each VPN:

For VPN_101:

```
! VPN VPN_101
crypto isakmp policy 10
 encryption aes
 hash sha256
 authentication pre-share
 group 14

crypto ipsec transform-set vpn_transform esp-aes esp-sha256-hmac

access-list 100 permit ip 10.98.128.0 0.0.3.255 172.28.11.0 0.0.0.255

crypto isakmp key ZA788I address 198.51.100.33

crypto map VPN_101 10 ipsec-isakmp
 set peer 198.51.100.33
 set transform-set vpn_transform
 match address 100

interface GigabitEthernet0/1
 crypto map VPN_101
```

For VPN_102:

```
! VPN VPN_102
crypto isakmp policy 10
 encryption aes
 hash sha256
 authentication pre-share
 group 14

crypto ipsec transform-set vpn_transform esp-aes esp-sha256-hmac

access-list 100 permit ip 10.98.128.0 0.0.3.255 172.28.12.0 0.0.0.255

crypto isakmp key AM285I address 198.51.100.34

crypto map VPN_102 10 ipsec-isakmp
 set peer 198.51.100.34
 set transform-set vpn_transform
 match address 100

interface GigabitEthernet0/1
 crypto map VPN_102
```


© 2024 Cisco and/or its affiliates. All rights reserved. Cisco Public

Please note that there's a typo in the Jinja2 template, specifically in the line where it says `set transform-setvpn_transform`. There should be a space before "vpn_transform". Here's the corrected line that should appear in the template:

```
set transform-set vpn_transform
```

Additionally, you might face an issue when applying two different crypto maps to the same interface. Usually, a physical interface only supports one crypto map. If you need to support multiple VPNs on the same interface, you would typically use the same crypto map name with different sequence numbers for each peer.

Here's how you can modify the second crypto map to use the same crypto map name with a different sequence number (assuming you want to use the crypto map name `VPN_MAP` for both):

For VPN_102 (with a revised crypto map name and sequence number):

```
! VPN VPN_102
crypto isakmp policy 10
 encryption aes
 hash sha256
 authentication pre-share
 group 14

crypto ipsec transform-set vpn_transform esp-aes esp-sha256-hmac

access-list 102 permit ip 10.98.128.0 0.0.3.255 172.28.12.0 0.0.0.255

crypto isakmp key AM285I address 198.51.100.34

crypto map VPN_MAP 20 ipsec-isakmp
 set peer 198.51.100.34
 set transform-set vpn_transform
 match address 102

interface GigabitEthernet0/1
 crypto map VPN_MAP
```

Notice that the access list number for VPN_102 has been changed to 102 to avoid conflict with the access list for VPN_101. The crypto map sequence number for VPN_102 has been set to 20, differentiating it from the sequence number 10 used for VPN_101. If you follow this approach, make sure that all your VPNs use the same crypto map name (`VPN_MAP` in this case) with different sequence numbers.

© 2024 Cisco and/or its affiliates. All rights reserved. Cisco Public

You 3:48 PM

Using the data from the below CSV data,

```
vpn_name,tunnel_interface,side_1_public_ip,source_network,source_mask,side_2_outside,tunnel_destination,destination_network,desti
VPN_101,GigabitEthernet0/1,203.0.113.101,10.98.128.0,0.0.3.255,GigabitEthernet1/1,198.51.100.33,172.28.11.0,0.0.0.255,ZA788I
VPN_102,GigabitEthernet0/1,203.0.113.102,10.98.128.0,0.0.3.255,GigabitEthernet1/1,198.51.100.34,172.28.12.0,0.0.0.255,AM285I
```

generate a configuration from each row based on the below jinja2 template

```
! VPN {{ vpn_name }}
crypto isakmp policy 10
 encryption aes
 hash sha256
 authentication pre-share
 group 14

crypto ipsec transform-set vpn_transform esp-aes esp-sha256-hmac

access-list 100 permit ip {{ source_network }} {{ source_mask }} {{ destination_network }} {{ destination_mask }}

crypto isakmp key {{ preshared_key }} address {{ tunnel_destination }}

crypto map {{ vpn_name }} 10 ipsec-isakmp
 set peer {{ tunnel_destination }}
 set transform-setvpn_transform
 match address 100

interface {{ tunnel_interface }}
 crypto map {{ vpn_name }}
```


© 2024 Cisco and/or its affiliates. All rights reserved. Cisco Public

Please note that there's a typo in the Jinja2 template, specifically in the line where it says `set transform-setvpn_transform`. There should be a space before "vpn_transform". Here's the corrected line that should appear in the template:

```
set transform-set vpn_transform
```

Additionally, you might face an issue when applying two different crypto maps to the same interface. Usually, a physical interface only supports one crypto map. If you need to support multiple VPNs on the same interface, you would typically use the same crypto map name with different sequence numbers for each peer.

Here's how you can modify the second crypto map to use the same crypto map name with a different sequence number (assuming you want to use the crypto map name `VPN_MAP` for both):

For VPN_102 (with a revised crypto map name and sequence number):

```
! VPN VPN_102
crypto isakmp policy 10
 encryption aes
 hash sha256
 authentication pre-share
 group 14

crypto ipsec transform-set vpn_transform esp-aes esp-sha256-hmac

access-list 102 permit ip 10.98.128.0 0.0.3.255 172.28.12.0 0.0.0.255

crypto isakmp key AM285I address 198.51.100.34

crypto map VPN_MAP 20 ipsec-isakmp
 set peer 198.51.100.34
 set transform-set vpn_transform
 match address 102

interface GigabitEthernet0/1
 crypto map VPN_MAP
```

Notice that the access list number for VPN_102 has been changed to 102 to avoid conflict with the access list for VPN_101. The crypto map sequence number for VPN_102 has been set to 20, differentiating it from the sequence number 10 used for VPN_101. If you follow this approach, make sure that all your VPNs use the same crypto map name (`VPN_MAP` in this case) with different sequence numbers.

© 2024 Cisco and/or its affiliates. All rights reserved. Cisco Public

Using AI to Generate Configurations





© 2024 Cisco and/or its affiliates. All rights reserved. Cisco Public

In closing...
Programmability...
Nothing To Be
Afraid Of!

© 2024 Cisco and/or its affiliates. All rights reserved. Cisco Public

What Did We Cover?

- Spreadsheet driven automation
- Aw CRUD, we gotta talk a little about APIs
- Source of Truth, it doesn’t have to be you anymore
- pyATS - How to no-code and automate networks
- Ansible the Hammer of Network Automation

© 2024 Cisco and/or its affiliates. All rights reserved. Cisco Public

Hank Preston

- Stay in touch:
  - Webex/Email: hapresto@cisco.com
  - Blogs: https://blogs.cisco.com/author/hankpreston

© 2024 Cisco and/or its affiliates. All rights reserved. Cisco Public

cisco Live!

Keynote Deep Dives

Wednesday
10:30am –11:30am

Experiences Amplified: How AI Can Fuel Better Employee and Customer Experiences

Level 1
Room 106

Smart, Secure, Seamless: Transforming Experiences with Next-Generation Networking

Level 2
Room 204

Harness a Bold New Era: Transform Data Centre and Service Provider Connectivity

Level 2
Room 203

Securing User to Application and Everything in Between

Level 2
Melbourne Room 2

Unlocking Digital Resilience through Unified Observability

The HUB
Centre Stage

Complete Your Session Evaluations

Complete a minimum of 4 session surveys and the Overall Event Survey to claim a **Cisco Live T-Shirt**.

Complete your surveys in the **Cisco Live mobile app**.

© 2024 Cisco and/or its affiliates. All rights reserved. Cisco Public

Continue your education

- Visit the Cisco Stand for related demos
- Book your one-on-one Meet the Expert meeting
- Attend the interactive education with DevNet, Capture the Flag, and Walk-in Labs
- Visit the On-Demand Library for more sessions at www.CiscoLive.com/on-demand

© 2024 Cisco and/or its affiliates. All rights reserved. Cisco Public



Thank you


cisco Live!
GO BEYOND
#CiscoLiveAPJC