

Unlocking Day2Ops Excellence

CISCO Live !

Nexus Dashboard Innovations for ACI & NX-OS N9K Fabrics

Camillo Rossi
Technical Marketing Engineer

Matthias Wessendorf
Principal Technical Marketing Engineer

Session ID: BRKDCN-3924

Cisco Webex App


Questions?

Use Cisco Webex App to chat with the speaker after the session

How

- 1 Find this session in the Cisco Live Mobile App
- 2 Click “Join the Discussion”
- 3 Install the Webex App or go directly to the Webex space
- 4 Enter messages/questions in the Webex space

Webex spaces will be moderated by the speaker until 14 November 2025.



<https://ciscolive.ciscoevents.com/ciscolivebot/#BRKDCN-3924>

Agenda

- 01 Day 2 Ops
- 02 Nexus Dashboard Overview
- 03 Features
- 04 Troubleshooting Demos
- 05 Conclusion

Day 2 OPS

Managing the Complete Lifecycle

Day
0

**Infrastructure
planning,
delivery and
installation**


Day
1

**Discover,
configure
and secure**

Day
2

**Assure,
monitor and
troubleshoot**

"The average cost of IT downtime is \$5,600 per minute" – Gartner



"Organizations that focus on proactive problem management can resolve issues 43% faster compared to reactive problem solving." – IDC (International Data Corporation)



What's happening on Day 2 and what needs to change?

Customer Challenges



Tools

Fragmented


- Too many tools addressing silo-ed visibility use cases
- Some are old, and some are expensive
- Different protocols/mechanisms



Analyze

Reactive

- Inconsistent API architecture
- Specialized knowledge required
- Difficult to root-cause issue, and often time too late to react to it




Insights

Limited

- Low data fidelity that is not actionable
- Lack of data correlation, don't get the full picture
- No dataplane visibility


Network Telemetry Frees the Data

Where Data Is Created




**As Much Useful Data
As Efficiently as Possible**

Where Data Is Useful



Storage &
analysis


Key Streaming Telemetry Characteristics



Nexus Dashboard Overview

Nexus Dashboard

Operations Use cases and highlights



Deploy



Manage




Analyze



Security and Segmentation



Interoperability



Unified data-center network operations

Visibility, analytics, troubleshooting tools, and compliance all in one place




Cisco Nexus® Dashboard
Physical or virtual cluster

Cisco Nexus 9000


Included with every
Cisco Nexus switch license




Standalone



Cisco ACI



Other NX-OS / IOS-XE / IOS-XR




*Partial Support

Nexus Dashboard


Nexus Dashboard Form Factors and scale



One Node pND - Up to 50 switches



Three Node pND - Up to 400 switches



Six Node pND - Up to 750 switches



One Node vND Data - Up to 25 switches



Three Node vND - Up to 50 switches



Six Node vND - Up to 200 switches

Nexus Dashboard – Green/Brown Field

LAN Fabric automation and/or onboarding for AI analytics

Classic

2 or 3-tier NX-OS architectures

VXLAN

BGP EVPN fabrics for Nexus & Catalyst (IOS-XE)

AI/ML

Fine-tuned network provisioning to transport AI/ML apps with the best performance

External & Inter-Fabric Networks

NX-OS, IOS-XE, XR & 3rd party networks mainly used to interconnect ACI, NX-OS, & Campus


IP fabrics for media

Fine-tuned network provisioning and monitoring for broadcasting and media

Routed

BGP-based CLOS NX-OS fabrics

ACI



LAN


Unified Connectivity (OOB or In-band)

Select the Streaming Telemetry Connectivity

Connectivity always to ND Data


Stream out Software Telemetry

Support for Traffic Analytics*



*No support for FT and flow troubleshooting jobs


The power of ONE Nexus fabric experience



Introducing Cisco Nexus ONE


Solution Components

- Zero trust networking and micro-segmentation based on endpoint / security groups
- Advanced service chaining and service redirection
- Administrative multi-tenancy
- Standards based inter-op with 3rd party networks using open networking protocols
- Integration with CI/CD pipelines with DevOps ready APIs



Unified Nexus Dashboard


Toward simplification and unification



ND Telemetry Architecture




Virtual form-factor
Physical form-factor



Telemetry Data Collection

Software Telemetry


- Software Telemetry allow devices to export data only with an initial subscription request
- Telemetry can collect any objects stored in the Data Management Engine(DME), i.e.
 - Interface and hardware statistics
 - Endpoints
 - Show commands output
 - Routing protocols information
- Real Time telemetry allows on-demand subscription of specific resources for a limited time



Telemetry Data Collection

Hardware Telemetry

- Hardware Telemetry exports data about
 - Flow Information
 - Flow Telemetry
 - Traffic Analytics (NetflowV9)
 - Packet Drops (Flow Telemetry Events)




*Traffic Analytics involves some CPU operations too

Telemetry Data Collection

Fabric Snapshots and Show Tech Collection


- Every 2 hours Insights performs a full snapshot of the fabric
- Every week* show tech is collected for all switches and controllers
- Data is stored for 30+ days in historical DB



*2 weeks if fabric has more than 100 switches

Bug Scan

show tech and signature based



Known bugs based on Cisco RN



Active bugs through digital signature




Cisco Nexus Dashboard

AI capabilities – What is here today!

Descriptive analysis

- Hardware conformance
- Software conformance
- Scale conformance
- Configuration compliance
- SAN Insights
- Delta analysis
- Automated bug scan
- Global Product Search
- Advisory reporting



Time series analysis

- Traffic analytics
- Interface consumption
- Energy Management analysis
- Optics (SFP) Failure Prediction
- Micro-burst detection

Inferential/Correlation analysis

- Root cause analysis
- Anomaly correlation

Features


Live UI/Feature Walkthrough

The remaining slides in this deck are for your reference

Demos

How to troubleshoot an application connectivity issue

Highlights and benefits



Monitor all flows for Congestion, Latency, Drops

Traffic Categorization


Pervasive Visibility

Detect potential issues faster

Historical flow data maintained for up to 7 days

Traffic Analytics

How it works




*TCP and UDP only, L3 flows only, no transit routing

Connectivity Analysis

Connectivity Analysis


On Demand Helper




Traces **all** possible forwarding paths between source and destination



Identifies if there are problems in the path and **where** the issues are



Helps narrowing down the root cause, running forwarding checks



Connectivity Analysis

Analysis Options

ELAM

Supported on: ACI;NX-OS

ELAM captures live traffic crossing the devices

Then a report will be generated and retrieved by ND

ELAM can provide additional information on why the packets are dropped

OAM

Supported on: NX-OS

OAM is a protocol that facilitates troubleshooting in VXLAN EVPN

The main goal is to understand if the path between two EPs is healthy

No real traffic between EP is required.
Can be generated by the devices

Consistency-Checker


Supported on: NX-OS

CC is a NX-OS utility that validates the consistency between the software and hardware tables

Can be used to detect a mis programming caused by a bug or an unexpected configuration

CICD Pipeline



Enhancing Change Management





Enhancing Change Management

See impact of intended changes

Model intended configuration




Enhancing Change Management



Enforcing Config Compliance

Configuration Compliance

Use Case Overview



Naming Convention

“VRF names shall end with _vrf”

Configuration Rules

“VRF shall be enforced”

Configuration Compliance using Insights

One option for each Use Case



Snapshot-based

Compares the current config against the selected snapshot, allowing or not the addition of new objects



Import-based

Compares the current config against a partial config, allowing or not the addition of new objects



Template-based

Verifies that the attributes of a set of selected objects match the criteria specified in a template




Manual

Verifies that the attributes of a set of selected objects match the criteria specified manually in the UI

Configuration and Segmentation Compliance

Use Case Overview



Segmentation

“PCI must not talk to non PCI”

SLA

“APP must talk to DB on 1433”

Traffic Restriction

“INET must not talk to WEB on ssh”



Firmware Update Analysis

Upgrading with Confidence

Typical Challenges



Assurance that all pre-requisites have been satisfied



Time required to run all pre-checks and post-checks




Complexity of analysis of potential issues in target release



Lack of visibility of potential impact

Upgrading with Confidence

Pre-Upgrade and Post-Upgrade



Pre-upgrade checks	
Physical interfaces	✓
Neighbors	✓
Routes	✓
Endpoints	✓
Capacity utilization	✓

Post-upgrade checks	
Physical interfaces	✓
Neighbors	✓
Routes	✓
Endpoints (lower number discovered)	✗
Capacity utilization	✓

Upgrading with Confidence

Pre-Upgrade and Post-Upgrade

- Pre-Upgrade Checks
- Version and Bug Info / Validation
- Advice about potential conditions that exist before upgrade (not just faults)
- Post-Upgrade Delta Analysis

- *Did I fix it? Did I break it? Did I change it?*

at exist

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

<


Open-Source Monitoring for Cisco ACI

Overview

- Built on Proven Technologies that you might be already using
 - Grafana for Visualization
 - Prometheus for Monitoring
 - Memgraph for Config Exploration
- Flexibility and Customization
- Comes preconfigured with several dashboards
 - EPGs, VLAN Usage and Contract Explore
 - Fabric and Node Capacity
 - Statistics about Interfaces, Routing Protocols, Power Usage
- Extremely light weight (can run on a small VM/Laptop)

To find out more

<https://github.com/datacenter/aci-monitoring-stack>



Conclusion

Conclusion

- Nexus Dashboard is the most comprehensive tool for operating Nexus 9000 fabrics. It can help with and not only:
 - Assurance
 - Conformance
 - Monitoring with Real Time Telemetry
 - Reporting
 - Compliance
 - Software and Change Management
- For highly customizable dashboard and basic inventory and statistics telemetry visibility, opensource tools are available and can combine with ND capabilities

Complete your session evaluations



Complete a minimum of 4 session surveys and the Overall Event Survey to claim a Cisco Live T-Shirt.



Earn up to 800 points by completing all surveys and climb the Cisco Live Challenge leaderboard.



Level up and earn exclusive prizes!



Complete your surveys in the Cisco Live Events app.

Continue your education



Visit the Cisco Stand for related demos



Book your one-on-one Meet the Expert meeting



Attend the interactive education with Capture the Flag, and Walk-in Labs



Visit the On-Demand Library for more sessions at www.CiscoLive.com/on-demand

Contact me at: Insert preferred comms method

Thank you

CISCO Live !

