

What is Cisco Doing in Quantum?

cisco Live !

An Introduction to Quantum Mechanics, Computing, and Networking

Tim Szigeti
Distinguished Engineer

Session ID: BRKETI-1401

Cisco Webex App

Questions?

Use Cisco Webex App to chat with the speaker after the session

How

- 1 Find this session in the Cisco Live Mobile App
- 2 Click “Join the Discussion”
- 3 Install the Webex App or go directly to the Webex space
- 4 Enter messages/questions in the Webex space

Webex spaces will be moderated by the speaker until 14 November 2025.



<https://ciscolive.ciscoevents.com/ciscolivebot/#BRKETI-1401>

Cisco's Mission for Quantum Networking

Our goal is to provide high-rate, high-fidelity entanglement distribution over a scalable, multi-tenant, multi-user architecture.



Agenda

- 01 Why build quantum networks
- 02 Intro to quantum mechanics
- 03 Intro to quantum computing
- 04 Implications of quantum computing on cybersecurity
- 05 Intro to quantum networking
- 06 What is Cisco doing in quantum?
- 07 Summary / Post-session quiz

Pre-Session Quiz

- 1) Why build quantum networks?
- 2) What are some of the special properties of quantum bits (qubits)?
- 3) What makes a quantum computer so fast?
- 4) Does quantum compute threaten RSA and AES?
- 5) What is Y2Q? And when do most experts expect it?
- 6) What are three requirements for quantum safety?
- 7) When do Australian networks need to be quantum safe?
- 8) Can you transmit information faster than light with quantum teleporting?
- 9) Will quantum networks replace classical networks?
- 10) What is Cisco researching and developing in quantum?

Why Build Quantum Networks?

Why Build Quantum Networks?

Quantum Cryptography

Quantum networks can be used to securely exchange cryptographic keys, as these are mathematically proven to detect and prevent eavesdropping

The most well-known method of this application is Quantum Key Distribution (QKD)



Why Build Quantum Networks?

Distributed Quantum Computing

Interconnecting quantum computers to collectively empower:

- Simulations:
 - Chemical/Molecular Engineering
 - Weather forecasting
 - Financial Modelling
 - Etc.
- Optimizations
- AI/ML
- Cryptography (i.e. decryption)



Why Build Quantum Networks?

Blind Quantum Computing

A privacy-preserving method in which a client can delegate a computation task to remote quantum computer(s) without disclosing the source data or algorithms

The results of the computations would likewise be private



Why Build Quantum Networks?

Network Clock Synchronization

A world-wide set of high-precision clocks connected by quantum networks could achieve ultra precise clock signals

Current accuracy: 10 ns to 500 ps

Quantum accuracy: $\leq 1\text{ps}$



Why Build Quantum Networks?

Distributed Sensing

Signals from distributed sensors can be combined via quantum networks to obtain higher-accuracy measurements than currently possible with classical network interconnections

E.g. Deep Space Telescope Array

Classical precision: $\pm 1/\sqrt{N}$

Quantum precision: $\pm 1/N$



Why Build Quantum Networks?

Quantum Money

The main security requirement of money is unforgeability

A quantum money scheme aims to fulfill this requirement by exploiting the no-cloning property of unknown quantum states




An Introduction to Quantum Mechanics

What is Quantum Mechanics?

Quantum mechanics is the field of physics that explains how subatomic objects simultaneously have the characteristics of both:

Particles—tiny pieces of matter, and

Waves—variations that transfer energy



Quantum Bits (Qubits)

Any quantum particle that can be measured and expressed as being in one of two discrete states

0 or 1


These can include:

electrons

photons


ions

etc.




Qubit Example: Electron Spin

- The spin of an electron can be used as a qubit
- For example:
 - An upwards spin could be used represent a 0
 - A downward spin could be used to represent 1



Angular Momentum

- Electron spin a function of an innate property called Angular Momentum
- And the spin isn't just up or down, but can be anywhere in between, along any axis (X, Y, or Z)



General Quantum State Formula

$$|\psi\rangle = a|0\rangle + \beta|1\rangle$$

General Quantum State Formula

$$|\psi\rangle = \alpha|0\rangle + \beta|1\rangle$$

Quantum State
represented by Psi

(Psi is the 23rd letter of
the Greek alphabet)

Alpha Ket 0
Alpha represents the
amplitude of state 0


(Alpha is the first letter of
the Greek alphabet)

Beta Ket 1
Beta represents the
amplitude of state 1

(Beta is the second letter of
the Greek alphabet)

Quantum State and Vectors

$$|\psi\rangle = a|0\rangle + \beta|1\rangle$$



$$\begin{bmatrix} 1 \\ 0 \end{bmatrix}$$


Vector 0

X-Axis
Coordinate

Y-Axis
Coordinate

$$\begin{bmatrix} 0 \\ 1 \end{bmatrix}$$

Vector 1



Quantum State and Vectors

$$|\psi\rangle = a|0\rangle + \beta|1\rangle = \begin{bmatrix} a \\ \beta \end{bmatrix}$$


X-Axis Coordinate

Y-Axis Coordinate


$$|\psi\rangle = 0.8|0\rangle + 0.6|1\rangle = \begin{bmatrix} 0.8 \\ 0.6 \end{bmatrix}$$

The square of the amplitude is the probability, and the sum of the probabilities must equal 1

$$\alpha^2 + \beta^2 = 1$$




The Bloch Sphere: A 3D Qubit Representation



Quantum Special Property: Superposition

As long a qubit is unobserved (i.e. unmeasured) it remains in a “superposition” of probabilities for 0 and 1


The instant a qubit is measured, the superposition will collapse into one of the two discrete states



Quantum Special Property: Superposition

As long a qubit is unobserved
(i.e. unmeasured) it remains in a
“superposition” of probabilities for
0 and 1

The instant a qubit is measured,
the superposition will collapse into
one of the two discrete states




Quantum Special Property: Entanglement

Entanglement is a physical relationship between qubits where they react to a change in the other(s) state instantaneously, regardless of how far apart

Multiple qubits can become entangled with each other


Current world records is 51 (physical) qubits



<https://www.newscientist.com/article/2382022-record-breaking-number-of-qubits-entangled-in-a-quantum-computer/>
<https://www.livescience.com/technology/computing/new-quantum-computing-milestone-smashes-entanglement-world-record>

Quantum Special Property: Entanglement

An Introduction to Quantum Mechanics




A. Einstein



B. Podolsky



N. Rosen



John Bell





Alain Aspect



John Clauser



Anton Zeilinger



2022 Nobel Prize in Physics

"for experiments with entangled photons, establishing the violation of Bell inequalities and pioneering quantum information science"

<https://www.nobelprize.org/prizes/physics/2022/summary/>

Quantum Special Property: Entanglement

If an entangled qubit is measured,
then entanglement is broken

The discrete state of the entangled
qubit will depend on the
entanglement operation that was
performed

The important point is that as one
entangled qubit changes state, its
counterpart(s) will instantaneously
reflect that change




Quantum Special Property: No Cloning

It can be mathematically proven that it is impossible to clone a qubit

The mathematical proof uses the logical method of “Proof by Contradiction”

A descriptive proof is that a qubit cannot be measured without collapsing, but you cannot copy something without reading/measuring it first




Quantum Special Property: No Cloning

It can be mathematically proven that it is impossible to clone a qubit

The proof is made via a “Proof by Contradiction”


Given: $|\psi\rangle = \alpha|0\rangle + \beta|1\rangle$,
Let $a = \alpha|0\rangle$ and $b = \beta|1\rangle$
 $|\psi\rangle = (a + b)$

Reference Slide




For any given Transformation (T): $T(a + b) = T(a) + T(b)$
Let us assume the transformation is a cloning operation

Quantum state: $|\psi\rangle = \alpha|0\rangle + \beta|1\rangle$
Simplified to: $|\psi\rangle = (a + b)$





An Introduction to Quantum Computing



Digital Circuits Quick Recap




Transistors



Logic Gates



Circuits




Quantum Gate Operation

Quantum Gates manipulate the Amplitude θ and/or the Phase Φ of the state vector

Quantum gates:

- take a superposition as an input
- rotate their possibilities, and
- produce another superposition as an output


Unlike most digital gates, quantum gates always have the same number of outputs as inputs



Quantum Universal Gate Set


X

Pauli-X Gate is a NOT operation; it will turn a spin-up state to a spin-down state, and vice versa.




Y

Pauli-Y Gate is also a NOT operation, but rotates around the Y-axis; it is similar to the X-gate, but different in phase.




Z

Pauli-Z Gate rotates around the Z-axis.




T

T gate rotates a qubit $\pi/4$ around the Z-axis.



H

Hadamard Gate sets the qubit into a superposition state of a 50/50 chance that it will end up as $|0\rangle$ or $|1\rangle$.





CNOT



The Controlled- NOT gate acts on 2 qubits, and performs the NOT operation on the second qubit only when the first qubit is $|1\rangle$, otherwise it leaves it unchanged.

Quantum NOT Gate (Pauli-X Gate)

Rotates π Radians (180°) Around the X-Axis




MATRIX VECTOR

$$\begin{bmatrix} 0 & 1 \\ 1 & 0 \end{bmatrix} \begin{bmatrix} 1 \\ 0 \end{bmatrix} \xrightarrow{\text{Row x Column}} \begin{bmatrix} 0 \times 1 + 1 \times 0 \\ 1 \times 1 + 0 \times 0 \end{bmatrix} = \begin{bmatrix} 0 \\ 1 \end{bmatrix}$$

NOT Gate Basis State $|0\rangle$ Basis State $|1\rangle$

T Gate

Rotates $\pi/4$ Radians (45°) Around the Z-Axis



MATRIX

$$\begin{bmatrix} 1 & 0 \\ 0 & e^{i\pi/4} \end{bmatrix}$$

T Gate

VECTOR

$$\begin{bmatrix} \alpha \\ \beta \end{bmatrix}$$




Basis State

$$\begin{bmatrix} \alpha|0\rangle \\ e^{i\pi/4} \beta|1\rangle \end{bmatrix}$$

Rotated position

Hadamard Gate


Rotates π Radians (180°) around an X-Y Diagonal Axis (to Set Itself to a 50/50 State)



$$|\psi\rangle = \frac{1}{\sqrt{2}} |0\rangle + \frac{1}{\sqrt{2}} |1\rangle$$


$$|\psi\rangle = 0.7071 |0\rangle + 0.7071 |1\rangle =$$

The square of the amplitude
is the probability,
and the sum of the probabilities equals 1



Two-Qubit Quantum Gate: Controlled NOT (CNOT) Gate

Part 1: Digital Gate Analogy



XOR Truth Table

Input A	Input B	Output
0	0	0
0	1	1
1	0	1
1	1	0

Input A	Input B	A	Output
0	0	0	0
0	1	0	1
1	0	1	1
1	1	1	0

Whenever A = 0,
the output is B

Whenever A = 1,
the output is NOT B

Therefore, A **CONTROLS**
the NOT function for B

Two-Qubit Quantum Gate: Controlled NOT (CNOT) Gate

Part 2: CNOT Gate Matrix and Truth Table



MATRIX

1	0	0	0
0	1	0	0
0	0	0	1
0	0	1	0

Controlled NOT Gate

CNOT Truth Table

Input	Output
00>	00>
01>	01>
10>	11>
11>	10>

In this example, q_1 **CONTROLS** the NOT function for q_0


Note: the CNOT gate operation entangles the qubits.

The state of control qubit will determine the state of the target qubit.

From this point forward, their fates are intertwined (i.e. entangled).

Quantum Circuits

Include Both Quantum Operators + Classical Computing



The number of output qubits always matches the number of input qubits

Measuring is a Classical Computing operation

IBM Quantum Composer

IBM Quantum Composer

Files

2 files

Name

Created

Untitled circuit

a minute ago

Untitled circuit

2 hours ago

New file

File

Edit

Inspect

View

Share

Untitled circuit

Saved

H

$\oplus$

$\otimes$

$\otimes$

$\otimes$

I

T

S

Z

$T^\dagger$

$S^\dagger$

P

RZ

$|0\rangle$

$|1\rangle$

$\sqrt{X}$

$\sqrt{X}^\dagger$

Y

RX

RY

U

RXX

RZZ

+ Add

q₀

q₁

q₂

c₃

H

$\oplus$

$\otimes$

$\otimes$

$\otimes$

$T^\dagger$

$S^\dagger$

P

RZ

$|0\rangle$

$|1\rangle$

$\sqrt{X}$

$\sqrt{X}^\dagger$

Y

RX

RY

U

RXX

RZZ

Measurement Probabilities

Q-sphere

Statevector

Computational basis states

000

0

10

20

30

40

50

60

70

80

90

100

Q-sphere

$\pi/2$

π

Phase

0

Amplitude

0

0.2

0.4

0.6

0.8

1

000

001

010

011

100

101

110

111

Computational basis states

Output state

$[1+0j, 0+0j, 0+0j, 0+0j, 0+0j, 0+0j, 0+0j, 0+0j]$




OpenQASM 2.0

Open in Quantum Lab

```
1 OPENQASM 2.0;
2 include "qelib1.inc";
3
4 qreg q[3];
5 creg c[3];
6
7 h q[0];
8 cx q[0],q[1];
9 measure q[0] -> c[0];
```

Quantum Parallelism

Number of Qubits





Number of States

$$2^1 = 2$$

$$2^2 = 4$$

$$2^3 = 8$$

Probability Base States and Initial Probabilities



Quantum Interference Manipulation

Another benefit that can be realized by quantum computing comes from manipulating interference

Interference may be

- constructive or
- destructive

Programmers of quantum algorithms (like Grover's and Shor's algorithms) endeavor to arrange qubits so that :




- **correct** answers generate **constructive interference**
- **incorrect** answers generate **destructive interference**

Remember: Probability = Amplitude²

$$|\psi\rangle = \alpha|0\rangle + \beta|1\rangle$$


Sums of the squares of probabilities must equal 1

$$\alpha^2 + \beta^2 = 1$$




Classical Computing Problem Solving

A classic computer needs to sequentially iterate through a problem until the correct result is found



Quantum Computing Problem Solving

Quantum computing can provide a single or small number of answers with the highest probability of being correct, which narrows down the search for the correct solution



Quantum Speed-Up


Well-designed quantum circuits can perform operations maximize quantum advantages and can thus exhibit significant speed-ups, as compared to their digital counterparts

Speed-ups may be:

- **Linear**
- **Quadratic**

Linear
 $y=x$

Quadratic
 $y=x^2$



Quantum Speed-Up

Well-designed quantum circuits can perform operations maximize quantum advantages and can thus exhibit significant speed-ups, as compared to their digital counterparts


Speed-ups may be:

- **Linear**
- **Quadratic**
- **Exponential**

Linear
 $y=x$

Quadratic
 $y=x^2$

Exponential
 $y=2^x$



Quantum Speed-Up

Well-designed quantum circuits can perform operations maximize quantum advantages and can thus exhibit significant speed-ups, as compared to their digital counterparts


Speed-ups may be:

- **Linear**
- **Quadratic**
- **Exponential**


Linear
 $y=x$

Quadratic
 $y=x^2$

Exponential
 $y=2^x$



- Classic Computer: 2,500 years
- Quantum Computer: 1 minute



$2^{127} = 1.7 \times 10^{38}$ values

170,000,000,000,000,000,000,000,000,000,000,000,000,000,000

How Much Faster is a Quantum Computer?

$$2^1 = 2$$

$$2^2 = 4$$

$$2^3 = 8$$

$$2^4 = 16$$

...

$$2^{10} = 1,024$$

...

$$2^{20} = 1,048,576$$

...

$$2^{127} = 1.7 \times 10^{38} \text{ (IBM Eagle)}$$

...

$$2^{275} = 10^{82} \text{ Number of Atoms in the Universe}$$

...

$$2^{1121} = 10^{337} \text{ (IBM Condor)}$$

What Do Quantum Computers Look Like?



External (IBM)




External (IBM)



Internal (IBM)

<https://newsroom.ibm.com/media-quantum-innovation>



Application

Classical Processing

Digital Processing

Analog Processing

Quantum Processing



Functions

Implications of Quantum Computing on Cybersecurity

Security-Concerning Quantum Algorithms

Grover's Algorithm

- searches an unstructured database (or an unordered list) for a specific result
- Exhibits **quadratic** speed-up vs. digital (classical compute)
- theoretically threatens **symmetric** key algorithms, such as the Advanced Encryption Standard (AES)




Shor's Algorithm:

- factorizes large numbers
- Exhibits **exponential** speed up over digital
- theoretically threatens the security of **asymmetric** key algorithms, such as the classical Public Key Infrastructure (PKI) including:
 - Diffie-Hellman (DH)
 - Elliptic Curve Cryptography (ECC), and
 - Elliptic Curve Diffie Hellman (ECDH)

$$N = \text{Prime 1} \times \text{Prime 2}$$




Grover's Algorithm Quantum Circuit



<https://www.techscience.com/jgc/v3n4/46224/pdf>

Grover's Algorithm: Classic vs. Quantum



Classic
Search

$f(\text{"red ball"})$ ► “Position 5” Worst Case: N searches

Quantum
Search

$f(\text{"Pos 2?"})$ ► “False”
⋮
 $f(\text{"Pos 5?"})$ ► “True”




Worst Case: $\sqrt{N}$ searches



- Grover's Algorithm uses amplitude amplification to return the correct result with high probability
- As such, with quantum parallelism and interference management, Grover's Algorithm becomes **quadratically** faster than its corresponding classical algorithm




Grover's Algorithm

Initial Probability Distribution






Grover's Algorithm

Probability Distribution after Round 1






Grover's Algorithm

Probability Distribution after Round 2






Grover's Algorithm

Probability Distribution after Round 3



Grover's Algorithm

Probability Distribution after Round 4



How many Qubits Are Required to Break RSA and AES?

Experts estimate that:

RSA-2048 requires a quantum computer with 1,600 logically-corrected qubits to be broken

AES-256 requires a quantum computer with 6,681 logically-corrected qubits to be broken



<https://arxiv.org/pdf/2505.15917>


<https://pqcrypto2016.jp/data/Langenberg-Grover-AES.pdf>

How Many Physical Qubits are Required to Produce a Logically-Corrected Qubit?

Qubits are notoriously fragile and extremely sensitive to the environment and can easily lose coherence (state)

The logical state of a qubit can be spread over many physical qubits to achieve Quantum Error Correction (QEC)

- In March 2023, Google realized a logical qubit (LQ) with just 49 physical qubits (PQ)
- In December 2023, Harvard scientists achieved the same result with just 48 qubits
- In February 2024, IBM achieved 12 logical qubits with 288 physical qubits (24 PQ/LQ)
- In April 2024, Microsoft and Quantinuum achieved 4 logical qubits with 30 physical qubits (7.5 PQ/LQ)



<https://blog.google/inside-google/message-ceo/our-progress-toward-quantum-error-correction/>

<https://thequantumrecord.com/quantum-computing/breakthrough-in-quantum-error-correction/>

<https://pmc.ncbi.nlm.nih.gov/articles/PMC10972743/>

<https://spectrum.ieee.org/microsoft-quantum-computer-quantinuum>

So, Really... How Many Qubits Are Required to Break AES?

Let's assume 561 physical qubits for one logically-corrected qubit (per [Gidney-2025](#))

AES-256 requires a quantum computer with 6,681 logically-corrected qubits to be broken

$(6681 * \sim 561) = 3,748,041$

But there's more to consider...



<https://arxiv.org/pdf/2505.15917>

<https://pqcrypto2016.jp/data/Langenberg-Grover-AES.pdf>

Grover's Achilles Heel: Quadratic Speed-Up

- Grover's algorithm only offers **quadratic** speed up, and does NOT parallelize well
- It is acknowledged that if an attacker had a quantum computer that can issue circa 2^{128} successive evaluations, then they could find the key with high probability
- However, in this attack model, even a 160-bit key (which would require circa 2^{80} successive evaluations), would be secure for all practical purposes
 - For example, even if we assume that the quantum computer could evaluate the encryption function in the absurdly fast time of 1 picosecond, the total of 2^{80} successive evaluations would require over 30,000 years to complete
- Any realistic security policy is not concerned with an attack that takes that long to perform



<https://eprint.iacr.org/2017/811.pdf>

Key Takeaway:


As such, AES-256 is considered quantum resistant, provided the key exchange is also secure (i.e. not via PKI)

But What About RSA? How many Qubits are required to Break RSA?

Experts estimate that:

RSA-2048 requires a quantum computer with 1,600 *logically-corrected* qubits to be broken

And that these could be expressed via
897,864 physical qubits



Key Takeaway: RSA is very much under threat by quantum computing!!!

<https://arxiv.org/pdf/2505.15917>

- Shor's algorithm exhibits **exponential** quantum speed-up, as compared to classical computing systems, and
- Quantum computers are **increasing** in size, while
- Quantum Error Correction circuits are **decreasing** in size

Y2Q, CRQC and SNDL


Years to Quantum (Y2Q) refers to the unknown number of years until Cryptographically Relevant Quantum Computers (CRQC) become available

A CRQC can compute prime factorizations in polynomial time, thereby rendering public key algorithms all but obsolete

However, an adversary can capture network traffic today in the hopes of decrypting it later with a CRQC; this is called a Store Now, Decrypt Later (SNDL) or Harvest Now Decrypt Later (HNDL) type of attack



How Far Off Is That?



How Many Y2Q?

Cloud Security Alliance:

- April 14, 2030

Global Risk Institute:

- ~50% of experts predict 15 years


White House / NIST

- “in the not-too-distant future”



2024 OPINION-BASED ESTIMATES OF THE LIKELIHOOD OF A DIGITAL QUANTUM COMPUTER ABLE TO BREAK RSA-2048 IN 24 HOURS, AS FUNCTION OF TIME

Range between average of an optimistic (top value) or pessimistic (bottom value) interpretation of the likelihood intervals indicated by the respondents



<https://cloudsecurityalliance.org/press-releases/2022/03/09/cloud-security-alliance-sets-countdown-clock-to-quantum/>
<https://globalriskinstitute.org/publication/2024-quantum-threat-timeline-report/>
<https://www.whitehouse.gov/briefing-room/statements-releases/2022/05/04/fact-sheet-president-biden-announces-two-presidential-directives-advancing-quantum-technologies/>

Post Quantum Cryptography (PQC) Overview

In August 2022, SIKE was cracked on a single core laptop in just one hour

Post Quantum Cryptography (PQC) is the study of cryptographic algorithms that are designed run on a classical computer but are resistant to attack from quantum computers

National Institute of Standards and Technology (NIST) is leading the standardization efforts for PQC

NIST

Post Quantum Crypto Standardization Process

Public-key encryption & exchange

Digital Signatures

Call for nominations – 20 Dec 2016

17

Round 2 Candidates – 30 Jan 2019

9

4

Round 3 Candidates – 22 Jul 2020

3


4

Round 4 Candidates – 05 Jul 2022

Standards – 2024

Classic McEliece
BIKE
HQC
SIKE

Quantum Key Distribution (QKD)




QKD has already been achieved over distances of 1000 km



QKD requires a direct connection because current optical switches would destroy the quantum effect.

A superior solution would be a Quantum Internet



Eve

QKE protocols like BB84, BBM92 & E91 measure received quantum states

An eavesdropper will be unable to read information encoded in a quantum state and any attempt at eavesdropping will be immediately detected by the sender and receiver

<https://phys.org/news/2023-06-scientists-km-quantum-key.html>

Three Requirements to be Quantum-Safe



- Management Plane
- Control Plane
- Data Plane




- Secure Firmware
- Secure Software
- Secure Runtime
- Secure Identity



The capabilities needed to replace and adapt to continually evolving cryptographic algorithms while preserving security and ongoing operations

Quantum-Safe Journey Maps




The Urgency of the Threat

In direct response to the quantum threat, governments are mandating application and infrastructure upgrades within the next few years

For example, this Australian Signal's Directorate has issued the following recommendations and timelines:

- By the end of 2026: Organizations are expected to have a refined plan for their PQC transition
- By the end of 2028: Organizations should commence their transition to PQC
- By the end of 2030: Organizations are advised to have completed their PQC transition


The private sector is moving even faster



<https://www.cyber.gov.au/business-government/secure-design/planning-for-post-quantum-cryptography>

Cisco Quantum-Ready Services

Mission: Empower our customers to proactively protect their organizations from emerging quantum threats, while enabling them to harness the massive transformative potential of quantum technologies to drive innovation and business growth.



An Introduction to Quantum Networking

Photonic Qubits

Photons can represent qubits, as well as electrons

Photons are more conducive to quantum networking than electrons (electrons are more conducive to computing)




The logical states of 0 or 1 are not determined by the spin of photons, but rather by their polarization

Horizontal Polarization $|1\rangle$

Vertical Polarization $|0\rangle$



Polarization Quick Recap





<https://www.olympus-lifescience.com/en/microscope-resource/primer/lightandcolor/polarization/>
<https://www.olympus-lifescience.com/en/microscope-resource/primer/java/polarizedlight/3dpolarized/>

How Are Photons Entangled?

The most common approach to generate entangled photons is via Spontaneous Parametric Down-Conversion (SPDC) in nonlinear crystals

SPDC is an instant optical process that converts one photon of higher energy into a pair of photons of lower energy



<https://www.nature.com/articles/s41377-021-00537-2>
<https://spectrum.ieee.org/entanglement-on-a-chip>
<https://www.nist.gov/image/non-linear-crystal>


Classical Optical Communication



Quantum Communication via Transporting



Primary Challenge to Quantum Transport



Rate decays exponentially
with distance

Can we amplify the signal?

No, because of the No Cloning Theorem

(Two-Way) Quantum Communication via Teleporting

Initial State



Quantum Communication via Teleporting

Step 1: Entangle a Pair of Photons and Send One to the Receiver



Quantum Communication via Teleporting

Step 2: Perform Another Entanglement Operation at the Sender

Note:
of

This step results in a teleportation
the **combination** of the states of
qubits Q and A to qubit B



Quantum Communication via Teleporting

Step 3: Perform a Bell State Measurement at the Sender

Note: The Bell State Measurement simultaneously:

- breaks the three-way entanglement,
- collapses the superposition of qubit A, and
- produces a result of 1 of 4 Bell States

Note: $\otimes$ is a mathematical notation for a tensor product; that is, a product of two quantum states, $|\psi\rangle$ and $|\phi\rangle$



The Four Bell States:

$|\phi^+\rangle = (1/\sqrt{2}) (|0\rangle \otimes |0\rangle + |1\rangle \otimes |1\rangle)$ represented by binary 00

$|\phi^-\rangle = (1/\sqrt{2}) (|0\rangle \otimes |0\rangle - |1\rangle \otimes |1\rangle)$ represented by binary 01

$|\psi^+\rangle = (1/\sqrt{2}) (|0\rangle \otimes |1\rangle + |1\rangle \otimes |0\rangle)$ represented by binary 10

$|\psi^-\rangle = (1/\sqrt{2}) (|0\rangle \otimes |1\rangle - |1\rangle \otimes |0\rangle)$ represented by binary 11

Quantum Communication via Teleporting

Step 4: Send the Bell State Measurement Result over a Classical Channel



The Four Bell States:

$|\Phi^+\rangle = (1/\sqrt{2}) (|0\rangle \otimes |0\rangle + |1\rangle \otimes |1\rangle)$ represented by binary 00

$|\Phi^-\rangle = (1/\sqrt{2}) (|0\rangle \otimes |0\rangle - |1\rangle \otimes |1\rangle)$ represented by binary 01

$|\Psi^+\rangle = (1/\sqrt{2}) (|0\rangle \otimes |1\rangle + |1\rangle \otimes |0\rangle)$ represented by binary 10

$|\Psi^-\rangle = (1/\sqrt{2}) (|0\rangle \otimes |1\rangle - |1\rangle \otimes |0\rangle)$ represented by binary 11

Quantum Communication via Teleporting

Step 5: Perform a Correction Operation on the Received Qubit (if necessary)



The Four Bell States:

$$|\Phi^+\rangle = (1/\sqrt{2}) (|0\rangle \otimes |0\rangle + |1\rangle \otimes |1\rangle)$$

$$|\Phi^-\rangle = (1/\sqrt{2}) (|0\rangle \otimes |0\rangle - |1\rangle \otimes |1\rangle)$$

$$|\Psi^+\rangle = (1/\sqrt{2}) (|0\rangle \otimes |1\rangle + |1\rangle \otimes |0\rangle)$$

$$|\Psi^-\rangle = (1/\sqrt{2}) (|0\rangle \otimes |1\rangle - |1\rangle \otimes |0\rangle)$$

represented by binary 00 → nothing to correct


represented by binary 01 → rotate around x-axis

represented by binary 10 → rotate around y-axis

represented by binary 11 → rotate around z-axis


Quantum Teleporting Switch

Providing Entanglement in the Network vs. the Endpoint




Extending Quantum Teleporting

Introducing Entanglement Swapping




Quantum Routers & Protocols

Two-Way Entanglement Distribution Network Example



Quantum Routers & Protocols


Two-Way Entanglement Distribution Network Example



Elementary Link Entanglements

Quantum Routers & Protocols


Two-Way Entanglement Distribution Network Example



Entanglement Swapping

Quantum Routers & Protocols


Two-Way Entanglement Distribution Network Example



End-to-End Entanglement

Quantum Routers & Protocols


Two-Way Entanglement Distribution Network Example



Network Failure Event

Quantum Routers & Protocols

Two-Way Entanglement Distribution Network Example



Reestablishing End-to-End Entanglement

What is Cisco doing in Quantum?

Key Engineering Challenges in Quantum Computing & Networking




Developing Larger
Quantum Computers
Current Record: 1121 qubits



Achieving Longer
Quantum Coherence
Current Record: 784 ms




Requiring Fewer Qubits
for Error Correction
Current Record: 7.5 PQ/LQ



Extending
Entanglement
Current Record: 248 km




Raising Operating
Temperatures



Achieving Longer
Quantum Memory



Improving Quantum
Transmission Fidelity



Planning & Modelling
Quantum Networks



Developing Quantum
Network Protocols



Lowering
Costs

Cisco's Primary areas of focus

Steps to Building a Quantum Internet

- 1) Research & Mathematical Modelling
- 2) Quantum Simulation & Emulation
- 3) Hardware & Software Development





Modelling a Unified Classical & Quantum Internet



“We are now with Quantum Internet where we were with the classical Internet in the 1960s”

The Cisco Research team has published several research papers on how can we design a network that can serve thousands and eventually millions of end nodes



<https://outshift.cisco.com/blog/making-a-quantum-ready-internet>
<https://arxiv.org/abs/2205.07507>


Planning Quantum Networks Over Existing Fiber Networks

In another paper, the Cisco Research team developed a framework to guide the first steps of planning a quantum network using the existing optical network infrastructure


This framework was formulated as an optimization problem

- Specifically, as an Integer Linear Programming (ILP) problem

<https://outshift.cisco.com/blog/first-steps-to-quantum-network-planning>
<https://arxiv.org/abs/2308.16264>



Quantum Network Digital Twin




Quantum Random Number Generator (QRNG)




Hardware
Development

- Random Number Generation (RNG) is an essential function for cryptography
- Current classical random number generators are not truly random, but rather **pseudo-random**
 - As these perform mathematical functions on an initial seed value
- Quantum states are **mathematically guaranteed** to be truly random
- Cisco has developed a hardware Quantum Random Number Generator (QRNG)
 - This hardware is also accessible via the Quantum Network Design Kit (QNDK)



Random bit string 001110101011110101001101010110...



Quantum Network Entanglement Chip


Enabling Quantum Teleportation between Quantum Endpoints



Hardware
Development



Quantum Teleportation Chip



Key Features:

- Miniaturized Photonic Integrated Chip (PIC) that **operates at room temperature**
- **Integrates with existing fiber optic infrastructure** by operating at standard telecom wavelengths
- **Delivers high-performance** by producing 1 million high-fidelity entanglement pairs per output channel, with a rate of up to 200 million entanglement pairs per second
- Consumes less than 1mW of power for **energy efficiency**

<https://blogs.cisco.com/news/quantum-networking-how-cisco-is-accelerating-practical-quantum-computing>


Network-Aware Quantum-Compiler

Developing the World's First Quantum Compiler




Hardware/Software
Co-Design

- We believe the most practical path to scalable quantum computing lies in distributed quantum computing, housed within a Quantum Data Center (QDC)
- Building a QDC requires a fundamental shift in how we design, manage, and operate quantum systems
- A key component of this vision is a distributed quantum computing compiler that explicitly understands and leverages network connectivity and inter-processor communication
- This industry-first compiler supports:
 - distributed quantum error correction
 - network-aware circuit partitioning
 - qubit mapping
 - advanced scheduling
 - multi-tenancy for QDCs




<https://outshift.cisco.com/blog/network-aware-quantum-compiler>

What are We Working on Now?



<https://research.cisco.com/quantum-research>

What are We Working on Now?



<https://research.cisco.com/quantum-research>

Summary

Post-Session Quiz

- 1) Why build quantum networks?
- 2) What are some of the special properties of quantum bits (qubits)?
- 3) What makes a quantum computer so fast?
- 4) Does quantum compute threaten RSA and AES?
- 5) What is Y2Q? And when do most experts expect it?
- 6) What are three requirements for quantum safety?
- 7) When do Australian networks need to be quantum safe?
- 8) Can you transmit information faster than light with quantum teleporting?
- 9) Will quantum networks replace classical networks?
- 10) What is Cisco researching and developing in quantum?

Post Session Quiz / Summary

1) Why build quantum networks?

Why Build Quantum Networks?

Quantum Cryptography

Quantum networks can be used to securely exchange cryptographic keys, as these are mathematically proven to detect and prevent eavesdropping

The most well-known method of this application is **Quantum Key Distribution (QKD)**



© 2025 Cisco and/or its affiliates. All rights reserved.

BRKETI-1401

7

© 2025 Cisco and/or its affiliates. All rights reserved.

Why Build Quantum Networks?

Distributed Quantum Computing

Interconnecting quantum computers to collectively empower:

- Simulations:
 - Chemical/Molecular Engineering
 - Weather forecasting
 - Financial Modelling
 - Etc.
- Optimization Logistics
- AI/ML
- Cryptography (i.e. Decryption)



© 2025 Cisco and/or its affiliates. All rights reserved.

BRKETI-1401

8

© 2025 Cisco and/or its affiliates. All rights reserved.

Why Build Quantum Networks?

Blind Quantum Computing

A privacy-preserving method in which a client can delegate a computation task to remote quantum computer(s) without disclosing the source data or algorithms

The results of the computations would likewise be private



© 2025 Cisco and/or its affiliates. All rights reserved.

BRKETI-1401

9

© 2025 Cisco and/or its affiliates. All rights reserved.

Why Build Quantum Networks?

Network Clock Synchronization

A world-wide set of high-precision clocks connected by quantum networks could achieve ultra precise clock signals

Current accuracy: 10 ns to 500 ps
Quantum accuracy: ≤ 1 ps



<https://www.nasa.gov/systems/docs/performance/accuracy/>
<https://newsroom.jhu.edu/documents/08256002>

© 2025 Cisco and/or its affiliates. All rights reserved.

BRKETI-1401

10

© 2025 Cisco and/or its affiliates. All rights reserved.

Why Build Quantum Networks?

Distributed Sensing

Signals from distributed sensors can be combined via quantum networks to obtain higher-accuracy measurements than currently possible with classical network interconnections

E.g. Deep Space Telescope Array

Classical precision: $\pm 1/\sqrt{N}$

Quantum precision: $\pm 1/N$



© 2025 Cisco and/or its affiliates. All rights reserved.

BRKETI-1401

11

© 2025 Cisco and/or its affiliates. All rights reserved.

Why Build Quantum Networks?

Quantum Money

The main security requirement of money is unforgeability

A quantum money scheme aims to fulfill by this requirement by exploiting the no-cloning property of unknown quantum states



© 2025 Cisco and/or its affiliates. All rights reserved.

BRKETI-1401

12


© 2025 Cisco and/or its affiliates. All rights reserved.

Post Session Quiz / Summary

2) What are some of the special properties of quantum bits (qubits)?

Quantum Special Property: Superposition

- As long a Qubit is unobserved (i.e. unmeasured) it is in a “Superposition” of probabilities for 0 and 1
- The instant a Qubit is measured, the superposition will collapse into one of the two discrete states




CISCO Live!

BRKETI-1301

© 2024 Cisco and/or its affiliates. All rights reserved. Cisco Public 23

Quantum Special Property: Entanglement

- Entanglement is a physical relationship between Qubits where they react to a change in the other(s) state instantaneously regardless of how far they are apart
- Multiple qubits can become entangled with each other
 - The current record is 54
- If an entangled Qbit is measured, then entanglement collapses



<https://www.newscentist.com/article/2362022-record-breaking-number-of-qubits-entangled-in-a-quantum-computer/>

CISCO Live!

BRKETI-1301

© 2024 Cisco and/or its affiliates. All rights reserved. Cisco Public 25

Quantum Special Property: No Cloning


Given: $|\psi\rangle = a|0\rangle + b|1\rangle$,
Let $a = a|0\rangle$ and $b = b|1\rangle$
 $|\psi\rangle = (a + b)$

- It can be mathematically proven that it is impossible to clone a qubit
- The proof uses the logical method of “Proof by Contradiction”

Quantum state: $|\psi\rangle = a|0\rangle + b|1\rangle$
Simplified to: $|\psi\rangle = (a + b)$



For any given Transformation (T): $T(a + b) = T(a) + T(b)$
Let us assume the transformation is a cloning operation




CISCO Live!

BRKETI-1301

© 2024 Cisco and/or its affiliates. All rights reserved. Cisco Public 27

Post Session Quiz / Summary

3) What makes a quantum computer so fast?




Interference Manipulation

- Another benefit that can be realized by quantum computing comes from manipulating interference
- Interference may be
 - **constructive** or
 - **destructive**
- Quantum algorithms (like Grover's and Shor's) endeavor to arrange qubits so that :
 - **correct** answers generate **constructive interference**
 - **incorrect** answers generate **destructive interference**
- Remember: Probability = Amplitude²

$$|\psi\rangle = \alpha|0\rangle + \beta|1\rangle$$

Sums of the squares of probabilities must equal 1

$$\alpha^2 + \beta^2 = 1$$



Post Session Quiz / Summary

4) Does quantum compute threaten RSA and AES?

The Implications of Quantum Computing on Cybersecurity

But What About RSA? How many Qubits are required to Break RSA?

Experts estimate that:

RSA-2048 requires a quantum computer with 1,600 *logically-corrected* qubits to be broken

And that these could be expressed via
897,864 physical qubits

Key Takeaway: RSA is very much under threat by quantum computing!!!

- Shor's algorithm exhibits **exponential** quantum speed-up, as compared to classical computing systems, and
- Quantum computers are *increasing* in size, while
- Quantum Error Correction circuits are *decreasing* in size

© 2025 Cisco and/or its affiliates. All rights reserved.

BRKETI-1401

64



<https://arxiv.org/pdf/2505.15917>

Grover's Achilles Heel: Quadratic Speed-Up

- Grover's algorithm only offers **quadratic** speed up, and does NOT parallelize well
- While it is acknowledged that if an attacker had a quantum computer that can issue circa 2^{128} successive evaluations then they could find the key with high probability
- However, in this attack model, even a 160-bit key (which would require circa 2^{80} successive evaluations), would be secure for all practical purposes
 - For example, even if we assume that the quantum computer could evaluate the encryption function in the absurdly fast time of 1 picosecond, the total of **2^{80} successive evaluations would require over 30,000 years to complete**
- Any realistic security policy is not concerned with an attack that takes that long to perform

Key Takeaway:

As such, AES-256 is considered quantum resistant, provided the key exchange is also secure (i.e. not via PKI)

cisco Live!

#CiscoLive

BRKETI-1401

© 2024 Cisco and/or its affiliates. All rights reserved. Cisco Public 58




<https://eprint.iacr.org/2017/811.pdf>

Post Session Quiz / Summary

5) What is Y2Q? And when do most experts expect it?

Y2Q, CRQC and SNDL

- Years to Quantum (Y2Q) refers to the unknown number of years before there are Cryptographically Relevant Quantum Computers (CRQC)
- A CRQC can compute prime factorizations and discrete logarithms in polynomial time by Shor's algorithm, thereby rendering public key algorithms all but obsolete
- However, an adversary can capture network traffic *today* in the hopes of decrypting it *later* with a CRQC; this is a **Store Now, Decrypt Later (SNDL)** type of attack, and means that sensitive data is vulnerable *right now* to future quantum threats
 - Sometimes this method is also referred to as **Harvest Now Decrypt Later (HNDL)**



cisco *Live!*


#CiscoLive

BRKETI-1401

© 2024 Cisco and/or its affiliates. All rights reserved. Cisco Public 59

How Many Y2Q?

- 1 • Cloud Security Alliance:
 - April 14, 2030
- 2 • Global Risk Inst:
 - ~50% within 15 years
- 3 • White House / NIST
 - “in the not-too-distant future”



<https://cloudsecurityalliance.org/press-releases/2022/03/09/cloud-security-alliance-sets-countdown-clock-to-quantum/>
<https://globalriskinstitute.org/publication/2023-quantum-threat-timeline-report/>
<https://www.whitehouse.gov/briefing-room/statements-releases/2022/05/04/fact-sheet-president-biden-announces-two-presidential-directives-advancing-quantum-technologies/>

cisco *Live!*

BRKETI-1301

© 2024 Cisco and/or its affiliates. All rights reserved. Cisco Public 53

Post Session Quiz / Summary

6) What are three key requirements to become quantum-safe?



- Management Plane
- Control Plane
- Data Plane



- Secure Firmware
- Secure Software
- Secure Runtime
- Secure Identity



The capabilities needed to replace and adapt to continually evolving cryptographic algorithms while preserving security and ongoing operations

Post Session Quiz / Summary

7) When do Australian networks need to be quantum-safe?

How to Become Quantum-Safe


The Urgency of the Threat

In direct response to the quantum threat, governments are mandating application and infrastructure upgrades within the next few years

For example, this Australian Signal's Directorate has issued the following recommendations and timelines:

- By the end of 2026: Organizations are expected to have a refined plan for their PQC transition
- By the end of 2028: Organizations should commence their transition to PQC
- By the end of 2030: Organizations are advised to have completed their PQC transition

The private sector is moving even faster



<https://www.cyber.gov.au/business-government/secure-design/planning-for-post-quantum-cryptography>

© 2025 Cisco and/or its affiliates. All rights reserved.

49




Post Session Quiz / Summary

8) Can you transmit information faster than light with quantum teleporting?

Key Takeaway:

Quantum teleportation does **NOT** enable faster than light communication



Equivalent to sending (at least) one bit over a classical channel

Teleporting one of 4 random states does occur faster than light, but (strictly speaking) this not an **information** transfer on its own merit, since we cannot correctly interpret what has been sent without additional data

(At least) Two more bits of data are sent over a classic channel


Post Session Quiz / Summary

9) Will quantum networks replace classical networks?


Key Takeaway:

Quantum teleportation does NOT enable faster than light communication


In fact, **for every bit** of information sent via **quantum** teleportation, **at least 3 additional bits of data must be sent over classical channels**



Equivalent to sending (at least) **one bit over a classical channel**



Teleporting one of 4 random states does occur faster than light, but (strictly speaking) this not an information transfer on its own merit, since we cannot correctly interpret what has been sent without additional data



(At least) **Two more bits of data are sent over a classic channel**

Post Session Quiz / Summary

10) What is Cisco researching and developing in quantum?

Modelling a Unified Classical & Quantum Internet

1 Research

- “We are now with Quantum Internet where we were with the classical Internet in the 1960s”
- The Cisco Research team has published a paper on how can we design a network that can serve thousands and eventually millions of end nodes

<https://outshift.cisco.com/blog/making-a-quantum-ready-internet>
<https://www.research.cisco.com/research-projects/quantum-ready-internet/>

BRKQSDJLW BRKETI-1401 © 2024 Cisco and/or its affiliates. All rights reserved. Cisco Public 89

Planning Quantum Networks Over Existing Fiber Networks

1 Research

- In another paper, the Cisco Research team developed a framework to guide the first steps of planning a quantum network using the existing optical network infrastructure
- This framework was formulated as an optimization problem
- Specifically as an Integer Linear Programming (ILP) problem

<https://outshift.cisco.com/blog/first-steps-to-quantum-network-planning>
<https://www.research.cisco.com/research-projects/quantum-ready-internet/>

BRKQSDJLW BRKETI-1401 © 2024 Cisco and/or its affiliates. All rights reserved. Cisco Public 90

Quantum Network Digital Twin

2 Simulation

<https://research.cisco.com/research-projects/quantum-ready-internet/>

BRKETI-1401 © 2025 Cisco and/or its affiliates. All rights reserved. Cisco Public 91

Quantum Random Number Generator (QRNG)

3 Hardware Development

- Random Number Generation (RNG) is an essential function for cryptography
- Current classical random number generators are not truly random, but rather pseudo-random
- As these perform mathematical functions on an initial seed value
- Quantum states are mathematically guaranteed to be truly random
- Cisco has developed a hardware Quantum Random Number Generator (QRNG)
- This hardware is also accessible via the Quantum Network Design Kit (QNDK)

Random bit string 001110101011110101001101010110...

BRKQSDJLW BRKETI-1401 © 2024 Cisco and/or its affiliates. All rights reserved. Cisco Public 92

Quantum Network Entanglement Chip

3 Hardware Development

Enabling Quantum Teleportation between Quantum Endpoints

Quantum Teleportation Chip

Alice Bob

Entangled Pair

Key Features:

- Miniaturized Photonic Integrated Chip (PIC) that operates at room temperature
- Integrates with existing fiber optic infrastructure by operating at standard telecom wavelengths
- Delivers high-performance by producing 1 million high-fidelity entanglement pairs per output channel, with a rate of up to 200 million entanglement pairs per second
- Consumes less than 1mW of power for energy efficiency

<https://blogs.cisco.com/news/quantum-networking-how-cisco-is-accelerating-practical-quantum-computing>

BRKQSDJLW BRKETI-1401 © 2025 Cisco and/or its affiliates. All rights reserved. Cisco Public 93

Network-Aware Quantum-Compiler

3 Hardware/Software Co-Design

Developing the World's First Quantum Compiler

- We believe the most practical path to scalable quantum computing lies in distributed quantum computing, housed within a Quantum Data Center (QDC)
- Building a QDC requires a fundamental shift in how we design, manage, and operate quantum systems
- A key component of this vision is a distributed quantum computing compiler that explicitly understands and leverages network connectivity and inter-processor communication
- This industry-first compiler supports:
 - distributed quantum error correction
 - network-aware circuit partitioning
 - qubit mapping
 - advanced scheduling
 - multi-tenancy for QDCs

Compiler


Network Protocols & Algorithms

<https://outshift.cisco.com/blog/network-aware-quantum-compiler>

BRKQSDJLW BRKETI-1401 © 2025 Cisco and/or its affiliates. All rights reserved. Cisco Public 94

Post Session Quiz / Summary


10) What is Cisco researching and developing in quantum?



<https://research.cisco.com/quantum-research>

Post Session Quiz / Summary

10) What is Cisco researching and developing in quantum?



<https://research.cisco.com/quantum-research>

Complete your session evaluations



Complete a minimum of 4 session surveys and the Overall Event Survey to claim a Cisco Live T-Shirt.



Earn up to 800 points by completing all surveys and climb the Cisco Live Challenge leaderboard.



Level up and earn exclusive prizes!



Complete your surveys in the Cisco Live Events app.

Continue your education



Visit the Cisco Stand for related demos



Book your one-on-one Meet the Expert meeting



Attend the interactive education with Capture the Flag, and Walk-in Labs



Visit the On-Demand Library for more sessions at www.CiscoLive.com/on-demand

Contact me at: szigeti@cisco.com

Thank you

CISCO Live !

