

Pig-in-the-middle

cisco Live !

TLS/QUIC Decryption, Encrypted Visibility Engine (and much more 😊)
Deep Dive on Cisco Secure Firewall

Christopher Grabowski
Technical Marketing Engineering
Technical Leader

Session ID: BRKSEC-3320

“The F-117 Nighthawk was a ‘silver bullet’, able to effortlessly penetrate the best-defended air spaces in the world by virtue of stealth”



Major Robert ‘Robson’ Donaldson describes taking the stealth fighter to war during Operation Desert Storm against Iraq.



With the evolving encryption stack, we may be soon finding ourselves staring at the radar – and realizing (OR NOT) it has gone dumb...



Security is just an obstacle course for an attacker



Without visibility, there is no security – the new encryption stack is making us blind

THE CHALLENGE: Security is Going Dark

- 50% of internet traffic now uses QUIC (bypasses TCP)
- Encrypted Client Hello (ECH) disables NGFW capabilities
- Certificate lifetimes dropping to 47 days by 2029
- Quantum computers will break current encryptions

THE SOLUTION: Cisco Secure Firewall Innovations

- ✓ QUIC decryption (GA) – inspect UDP-based encrypted traffic
- ✓ EVE (ML Engine) – detects threats and Apps without decryption
- ✓ Shadow Traffic Detection – find evasion attempts
- ✓ PQC ready hardware and automation enhancements

YOUR OUTCOMES TODAY

- Maintain visibility despite encryption trends
- Simplify decryption policy and automate certificate lifecycle
- Build awareness and sharpen your crypto-skills
- Plan ahead and build your readiness roadmap

Agenda

- 01 Introduction**
- 02 TLS Handshake Walkthrough**
- 03 The New Decryption UI**
- 04 QUIC and EVE Updates**
- 05 Detecting Shadow Traffic**
- 06 Encrypted Client Hello**
- 07 Certificate Management**
- 08 Post Quantum vs. TLS**

Cisco Webex App


Questions?

Use Cisco Webex App to chat with the speaker after the session

How

- 1 Find this session in the Cisco Live Mobile App
- 2 Click “Join the Discussion”
- 3 Install the Webex App or go directly to the Webex space
- 4 Enter messages/questions in the Webex space

Webex spaces will be moderated by the speaker until 14 November 2025.



<https://ciscolive.ciscoevents.com/ciscolivebot/#BRKSEC-3320>

Your Speaker



Christopher Grabowski
Technical Marketing Engineer
CCIE Security #42466

Based in Warsaw, Poland

With Cisco since May 2012

Started with TAC Security, then Advanced Services,
now Technical Marketing Engineer

Focusing on Identity Firewall, Integrations and
TLS Decryption

Enjoys cooking and spending time with the family

WARNING !

This presentation may cause elevated geek levels over an extended period of time

VIEWER DISCRETION IS ADVISED


TLS Handshake

TLS 1.3 Handshake At a Glance




Firewall enforcement heavily relies on this single TLS extension

	Time	Source	SPORT	Destination	DPORT	Protocol	Length	Info
1	0.000000	172.16.136.96	49934	18.239.83.46	443	TCP	66	49934 → 443 [SYN] Seq=0 Win=64240 Len=0 MSS=1460
2	0.000500	18.239.83.46	443	172.16.136.96	49934	TCP	66	443 → 49934 [SYN, ACK] Seq=0 Ack=1 Win=65535 Len=
3	0.000547	172.16.136.96	49934	18.239.83.46	443	TCP	54	49934 → 443 [ACK] Seq=1 Ack=1 Win=2097408 Len=0
4	0.000780	172.16.136.96	49934	18.239.83.46	443	TLSv1.3	585	Client Hello (SNI=www.onet.pl)



TLS 1.3 Handshake At a Glance



How quickly does Snort stop inspecting connections?

With decryption enabled, Snort continued inspection (column available in 7.7+) for 10s of packets.

Event Type	Action	Source IP	Destination IP	Destination Port / ICMP Code	TLS Client SNI	Inspected Packets	TLS Actual Action	EVE Process Name
↔ Connection	➡ Allow	172.16.136.96	18.239.83.82	443 (https) / tcp	www.onet.pl	21	Decrypt (Resign)	chromium browser
↔ Connection	➡ Allow	172.16.136.96	18.239.83.82	443 (https) / tcp	www.onet.pl	76	Decrypt (Resign)	chromium browser

Without decryption, the inspection stops after only 4 packets

Event Type	Action	Source IP	Destination IP	Destination Port / ICMP Code	TLS Client SNI	Inspected Packets	TLS Actual Action	EVE Process Name
↔ Connection	➡ Allow	172.16.136.96	18.239.83.46	443 (https) / tcp	www.onet.pl	4	Do Not Decrypt	chromium browser
↔ Connection	➡ Allow	172.16.136.96	18.239.83.46	443 (https) / tcp	www.onet.pl	4	Do Not Decrypt	chromium browser

... and the firewall looks at the TCP handshake the initial TLS message from the client:

	Time	Source	SPORT	Destination	DPORT	Protocol	Length	Info
1	0.000000	172.16.136.96	49934	18.239.83.46	443	TCP	66	49934 → 443 [SYN] Seq=0 Win=64240 Len=0 MSS=1460
2	0.000500	18.239.83.46	443	172.16.136.96	49934	TCP	66	443 → 49934 [SYN, ACK] Seq=0 Ack=1 Win=65535 Len=0
3	0.000547	172.16.136.96	49934	18.239.83.46	443	TCP	54	49934 → 443 [ACK] Seq=1 Ack=1 Win=2097408 Len=0
4	0.000780	172.16.136.96	49934	18.239.83.46	443	TLSv1.3	585	Client Hello (SNI=www.onet.pl)

Without decryption, we are essentially blind after the initial handshake...

Inspection scope without TLS/QUIC decryption.

(4 packets ...)


Wireshark packet capture (HTTPs connection to https://onet.pl)

Time	Source	SPORT	Destination	DPORT	Protocol	Length	Info
1 0.000000	172.16.136.96	49934	18.239.83.46	443	TCP	66	49934 → 443 [SYN] Seq=0 Win=64240 Len=0 MSS=1460 WS=256 SACK_PERM
2 0.000000	18.239.83.46	443	172.16.136.96	49934	TCP	66	443 → 49934 [SYN, ACK] Seq=0 Win=65535 Len=0 MSS=1380 WS=64 SACK_PERM
3 0.000547	172.16.136.96	49934	18.239.83.46	443	TCP	54	49934 → 443 [ACK] Seq=1 Ack=1 Win=2097408 Len=0
4 0.000780	172.16.136.96	49934	18.239.83.46	443	TLvSv1.3	585	Client Hello (SN=www.onet.pl)
5 0.002136	18.239.83.46	443	172.16.136.96	49934	TCP	60	443 → 49934 [ACK] Seq=1 Ack=532 Win=64960 Len=0
6 0.142588	18.239.83.46	443	172.16.136.96	49934	TLvSv1.3	1414	Server Hello, Change Cipher Spec, Application Data
7 0.142588	18.239.83.46	443	172.16.136.96	49934	TCP	1414	443 → 49934 [ACK] Seq=1361 Ack=532 Win=64960 Len=1360 [TCP PDU reassembled in 8]
8 0.142588	18.239.83.46	443	172.16.136.96	49934	TLvSv1.3	800	Application Data, Application Data, Application Data
9 0.142630	172.16.136.96	49934	18.239.83.46	443	TCP	54	49934 → 443 [ACK] Seq=532 Ack=3467 Win=2097408 Len=0
10 0.144132	172.16.136.96	49934	18.239.83.46	443	TLvSv1.3	118	Change Cipher Spec, Application Data
11 0.144272	172.16.136.96	49934	18.239.83.46	443	TLvSv1.3	146	Application Data
12 0.144402	172.16.136.96	49934	18.239.83.46	443	TLvSv1.3	538	Application Data
13 0.145355	18.239.83.46	443	172.16.136.96	49934	TCP	60	443 → 49934 [ACK] Seq=3467 Ack=596 Win=64896 Len=0
14 0.145433	18.239.83.46	443	172.16.136.96	49934	TCP	60	443 → 49934 [ACK] Seq=3467 Ack=688 Win=64832 Len=0
15 0.145433	18.239.83.46	443	172.16.136.96	49934	TCP	60	443 → 49934 [ACK] Seq=3467 Ack=1172 Win=64320 Len=0
16 0.156974	18.239.83.46	443	172.16.136.96	49934	TLvSv1.3	304	Application Data, Application Data
17 0.157080	172.16.136.96	49934	18.239.83.46	443	TLvSv1.3	85	Application Data
18 0.157585	18.239.83.46	443	172.16.136.96	49934	TCP	60	443 → 49934 [ACK] Seq=3717 Ack=1203 Win=64320 Len=0
19 0.166547	18.239.83.46	443	172.16.136.96	49934	TCP	1414	443 → 49934 [ACK] Seq=3717 Ack=1203 Win=64320 Len=1360 [TCP PDU reassembled in 33]
20 0.166547	18.239.83.46	443	172.16.136.96	49934	TCP	1414	443 → 49934 [ACK] Seq=5077 Ack=1203 Win=64320 Len=1360 [TCP PDU reassembled in 33]
21 0.166547	18.239.83.46	443	172.16.136.96	49934	TCP	1414	443 → 49934 [ACK] Seq=6437 Ack=1203 Win=64320 Len=1360 [TCP PDU reassembled in 33]
22 0.166547	18.239.83.46	443	172.16.136.96	49934	TCP	1414	443 → 49934 [ACK] Seq=7797 Ack=1203 Win=64320 Len=1360 [TCP PDU reassembled in 33]
23 0.166547	18.239.83.46	443	172.16.136.96	49934	TCP	1414	443 → 49934 [ACK] Seq=9157 Ack=1203 Win=64320 Len=1360 [TCP PDU reassembled in 33]
24 0.166547	18.239.83.46	443	172.16.136.96	49934	TCP	1414	443 → 49934 [ACK] Seq=10517 Ack=1203 Win=64320 Len=1360 [TCP PDU reassembled in 33]
25 0.166547	18.239.83.46	443	172.16.136.96	49934	TCP	222	443 → 49934 [PSH, ACK] Seq=11877 Ack=1203 Win=64320 Len=168 [TCP PDU reassembled in 33]
26 0.166547	18.239.83.46	443	172.16.136.96	49934	TCP	1414	443 → 49934 [ACK] Seq=12045 Ack=1203 Win=64320 Len=1360 [TCP PDU reassembled in 33]
27 0.166547	18.239.83.46	443	172.16.136.96	49934	TCP	1414	443 → 49934 [ACK] Seq=13405 Ack=1203 Win=64320 Len=1360 [TCP PDU reassembled in 33]
28 0.166547	18.239.83.46	443	172.16.136.96	49934	TCP	1294	443 → 49934 [PSH, ACK] Seq=14705 Ack=1203 Win=64320 Len=1240 [TCP PDU reassembled in 33]
29 0.166547	18.239.83.46	443	172.16.136.96	49934	TCP	1053	443 → 49934 [PSH, ACK] Seq=16005 Ack=1203 Win=64320 Len=999 [TCP PDU reassembled in 33]
30 0.166594	172.16.136.96	49934	18.239.83.46	443	TCP	54	49934 → 443 [ACK] Seq=1203 Ack=17004 Win=2097408 Len=0
31 0.174644	18.239.83.46	443	172.16.136.96	49934	TCP	1414	443 → 49934 [ACK] Seq=17004 Ack=1203 Win=64320 Len=1360 [TCP PDU reassembled in 33]
32 0.174644	18.239.83.46	443	172.16.136.96	49934	TCP	1414	443 → 49934 [ACK] Seq=18364 Ack=1203 Win=64320 Len=1360 [TCP PDU reassembled in 33]
33 0.174644	18.239.83.46	443	172.16.136.96	49934	TLvSv1.3	1414	Application Data
34 0.174644	18.239.83.46	443	172.16.136.96	49934	TCP	1414	443 → 49934 [ACK] Seq=21884 Ack=1203 Win=64320 Len=1360 [TCP PDU reassembled in 48]
35 0.174644	18.239.83.46	443	172.16.136.96	49934	TCP	1414	443 → 49934 [ACK] Seq=22444 Ack=1203 Win=64320 Len=1360 [TCP PDU reassembled in 48]
36 0.174644	18.239.83.46	443	172.16.136.96	49934	TCP	382	443 → 49934 [PSH, ACK] Seq=23804 Ack=1203 Win=64320 Len=328 [TCP PDU reassembled in 48]
37 0.174644	18.239.83.46	443	172.16.136.96	49934	TCP	1242	443 → 49934 [PSH, ACK] Seq=24132 Ack=1203 Win=64320 Len=1188 [TCP PDU reassembled in 48]
38 0.174679	172.16.136.96	49934	18.239.83.46	443	TCP	54	49934 → 443 [ACK] Seq=1203 Ack=25320 Win=2097408 Len=0
39 0.175164	18.239.83.46	443	172.16.136.96	49934	TCP	1414	443 → 49934 [ACK] Seq=25320 Ack=1203 Win=64320 Len=1360 [TCP PDU reassembled in 48]
40 0.175301	18.239.83.46	443	172.16.136.96	49934	TCP	1414	443 → 49934 [ACK] Seq=26680 Ack=1203 Win=64320 Len=1360 [TCP PDU reassembled in 48]
41 0.175301	18.239.83.46	443	172.16.136.96	49934	TCP	898	443 → 49934 [PSH, ACK] Seq=28040 Ack=1203 Win=64320 Len=844 [TCP PDU reassembled in 48]
42 0.175320	172.16.136.96	49934	18.239.83.46	443	TCP	54	49934 → 443 [ACK] Seq=1203 Ack=28884 Win=2097408 Len=0
43 0.183471	18.239.83.46	443	172.16.136.96	49934	TCP	1414	443 → 49934 [ACK] Seq=28884 Ack=1203 Win=64320 Len=1360 [TCP PDU reassembled in 48]
44 0.183471	18.239.83.46	443	172.16.136.96	49934	TCP	1414	443 → 49934 [ACK] Seq=30244 Ack=1203 Win=64320 Len=1360 [TCP PDU reassembled in 48]
45 0.183471	18.239.83.46	443	172.16.136.96	49934	TCP	1180	443 → 49934 [PSH, ACK] Seq=31604 Ack=1203 Win=64320 Len=1126 [TCP PDU reassembled in 48]
46 0.183471	18.239.83.46	443	172.16.136.96	49934	TCP	1414	443 → 49934 [ACK] Seq=32730 Ack=1203 Win=64320 Len=1360 [TCP PDU reassembled in 48]
47 0.183471	18.239.83.46	443	172.16.136.96	49934	TCP	1414	443 → 49934 [ACK] Seq=34090 Ack=1203 Win=64320 Len=1360 [TCP PDU reassembled in 48]
48 0.183471	18.239.83.46	443	172.16.136.96	49934	TLvSv1.3	1414	Application Data
49 0.183471	18.239.83.46	443	172.16.136.96	49934	TCP	444	443 → 49934 [PSH, ACK] Seq=36810 Ack=1203 Win=64320 Len=390 [TCP PDU reassembled in 66]
50 0.183471	18.239.83.46	443	172.16.136.96	49934	TCP	1242	443 → 49934 [PSH, ACK] Seq=37200 Ack=1203 Win=64320 Len=1188 [TCP PDU reassembled in 66]
51 0.183471	18.239.83.46	443	172.16.136.96	49934	TCP	1414	443 → 49934 [ACK] Seq=38388 Ack=1203 Win=64320 Len=1360 [TCP PDU reassembled in 66]
52 0.183514	172.16.136.96	49934	18.239.83.46	443	TCP	54	49934 → 443 [ACK] Seq=1203 Ack=39748 Win=2097408 Len=0
53 0.183541	18.239.83.46	443	172.16.136.96	49934	TCP	1414	443 → 49934 [ACK] Seq=39748 Ack=1203 Win=64320 Len=1360 [TCP PDU reassembled in 66]
54 0.183541	18.239.83.46	443	172.16.136.96	49934	TCP	898	443 → 49934 [PSH, ACK] Seq=41108 Ack=1203 Win=64320 Len=844 [TCP PDU reassembled in 66]
55 0.183551	172.16.136.96	49934	18.239.83.46	443	TCP	54	49934 → 443 [ACK] Seq=1203 Ack=41952 Win=2097408 Len=0
56 0.191339	18.239.83.46	443	172.16.136.96	49934	TCP	1414	443 → 49934 [ACK] Seq=41952 Ack=1203 Win=64320 Len=1360 [TCP PDU reassembled in 66]
57 0.191339	18.239.83.46	443	172.16.136.96	49934	TCP	1414	443 → 49934 [ACK] Seq=43312 Ack=1203 Win=64320 Len=1360 [TCP PDU reassembled in 66]
58 0.191362	172.16.136.96	49934	18.239.83.46	443	TCP	54	49934 → 443 [ACK] Seq=1203 Ack=44672 Win=2097408 Len=0
59 0.191418	18.239.83.46	443	172.16.136.96	49934	TCP	1414	443 → 49934 [ACK] Seq=44672 Ack=1203 Win=64320 Len=1360 [TCP PDU reassembled in 66]
60 0.191418	18.239.83.46	443	172.16.136.96	49934	TCP	1414	443 → 49934 [ACK] Seq=46032 Ack=1203 Win=64320 Len=1360 [TCP PDU reassembled in 66]

With decryption, Snort disengages after preempting all checks.

(as many packets as needed)

Understanding a QUIC session handshake



TLS Handshake – Key Takeaways

- SNI is visible in cleartext and drives 80%+ of security stack decisions
- TLS 1.3 and QUIC protect most of the handshake, but SNI remains exposed
- Without decryption, inspection drops after ~4 packets (vs. full session with decryption)
- QUIC uses TLS 1.3 natively, eliminates TCP 3-way handshake and has its own flow control

Revamped Decryption User Interface

The New Simplified Decryption Configuration Workflow

Rule-based Decryption Policy

#	Name	Dest Networks	Applications	Categories	SSL	Action
Administrator Rules						
This category is empty						
Standard Rules						
1	Inbound-Decrypt-1160dfed2	QUIC-Server	any	any	1 Cert Status selection	Decrypt - Replace Cert
2	Block-Certificate-Status	any	any	any	3 Cert Status selections	Block with reset
3	Block-TLS-Version	any	any	any	3 Protocol Versions	Block with reset
4	Bypass-Trusted-Connections	any	any	Any (Except Uncatego	1 Client Threat selection	Do not decrypt
5	Bypass-Undecryptable-Sites (Disabled)	any	any	any	1 DN selection	Do not decrypt
6	Bypass-Apps	any	YouTube YouTube Kids YouTube Music YouTube TV (6 more...)	any	any	Do not decrypt
7	Bypass-Undecryptable-Apps	any	Tags: undecryptable	any	any	Do not decrypt
8	Bypass-Categories	any	any	Finance (Any reputatio Health and Medicine (/ Online Trading (Any re;	any	Do not decrypt
9	Outbound-Decrypt-8fda97de48	any	any	any	any	Decrypt - Resign
Root Rules						
This category is empty						
Default Action						Do not decrypt

Traditional, granular mode for specialized configurations.

Standard Decryption Policy

Standard Decryption Policy

Nice and easy :)

Inbound Decryption

Enabled

Security zones

Source zones *
OutZone

Destination zones *
InZone1

Internal server details

Internal certificate object
QUIC-Server

Destination network object
QUIC-Server

Destination port object
HTTPS-UDP (optional)

Outbound Decryption

Enabled

Security zones

Source zones *
InZone1

Destination zones *
OutZone

Decrypt networks and users

Source network objects
Corporate-LAN

Users
any

Internal certificate authority *

TLS_Decrypt_SubCA



No ruleset to manage, simple guided configuration with predefined bypasses!

The New Simplified Decryption Configuration Workflow

Rule-based Decryption Policy

Custom DND Exceptions for Inbound (IP/Port based)

Known Key – Server Protection (IP/Port based)

Custom DND Exceptions / Bypass for Outbound (IP/Port based)

Custom DND Exceptions for Outbound
(Specific: URLs, DNS, Applications)

Do Not Decrypt (DND) Undecryptable, Pinned, Legally Prohibited
(URL Categories, Application Groups, DN Lists)

Key Resign – Outbound Client Protection
(URL Categories, Application Groups)

Default Do Not Decrypt

- Classic, **granular rule-by-rule control**
- **Requires careful rule ordering** to avoid decryption conflicts
- Recommended for **complex and exceptional use-cases**

Standard Decryption Policy

The screenshot displays the Standard Decryption Policy configuration interface, organized into several panels:

- Inbound Decryption:** Enabled. Security zones: Source zones (OutZone), Destination zones (InZone1). Internal server details: Internal certificate object (QUIC-Server), Destination network object (QUIC-Server), Destination port object (HTTPS-UDP). + Add new
- Outbound Decryption:** Enabled. Security zones: Source zones (InZone1), Destination zones (OutZone). Decrypt networks and users: Source network objects (Corporate-LAN), Users (dCloudRealm / Users). Internal certificate authority: TLS_Decrypt_SubCA. + Create new
- Intelligent Decryption Bypass:** Enabled. Recommended. Do not decrypt traffic for very low-risk clients connecting to trusted servers, based on the threat confidence levels of clients which is determined by the Encrypted Visibility Engine (EVE) and the URL Category Reputation. The device to which this policy is deployed must run version 7.7 or later and must have a valid IPS license.
- Bypass applications:** Known undecryptable applications: Bypass decryption of known undecryptable applications (checked). Selected applications and filters: YouTube, YouTube Kids, YouTube Music.
- Bypass URL categories:** URL category, Reputation. Finance (Any), Online Trading (Any), Health and Medicine (Any), Advertisements (Favorable & above).
- Block connections:** Block based on TLS version (checked). SSL v3.0, TLS v1.0, TLS v1.1. Block based on certificate status (checked). Invalid Signature, Expired, Not Yet Valid.

- **Single-page** setup with a clear, **intuitive workflow**
- Organised, **tiled layout** for inbound, outbound, bypass, and block policies
- Rule order automatically managed – **focus on intent, not sequence**

Decryption Policy in 4 Simple Steps

Step 1: Specify your servers for decryption

Inbound Decryption ☒ Enabled

Security zones ⓘ
Source zones *
OutZone

Destination zones *
InZone1

Edit

Internal server details ⓘ
Q Search

Internal certificate object	Destination network object	Destination port object
QUIC-Server	QUIC-Server	HTTPS-UDP

+ Add new

Step 2: Set protected networks and users

Outbound Decryption ☒ Enabled

Security zones ⓘ
Source zones *
InZone1

Destination zones *
OutZone

Edit

Decrypt networks and users ⓘ
Q Search

Source network objects

Users

Corporate-LAN

dCloudRealm / Users

+ Add new

Internal certificate authority * ⓘ
TLS_Decrypt_SubCA ⓘ ⓘ

+ Create new



Automatic ordering

Inbound Decryption

Block Insecure Handshake

Bypass Decryption

Outbound Decryption

Decryption
verdict

TLS
Handshake

Step 4: Block weak ciphers and bad certificates

Block connections ⓘ

☒ Block based on TLS version ⓘ
SSL v3.0 x TLS v1.0 x TLS v1.1 x

☒ Block based on certificate status ⓘ
Invalid Signature x Expired x Not Yet Valid x

Step 3: Exempt Apps, URLs, Users etc...

Bypass applications ⓘ

Known undecryptable applications
☒ Bypass decryption of known undecryptable applications ⓘ

Selected applications and filters

Application
YouTube
YouTube Kids

Bypass URL categories ⓘ

URL category	Reputation
Finance	Any
Online Trading	Any
Health and Medicine	Any
Advertisements	Favorable & above

Intelligent Decryption Bypass ⓘ

☒ Enabled ☒ Recommended

Do not decrypt traffic for very low-risk clients connecting to trusted servers, based on the threat confidence levels of clients which is determined by the Encrypted Visibility Engine (EVE) and the URL Category Reputation. The device to which this policy is deployed must run version 7.7 or later and must have a valid IPS license.

Bypass users ⓘ

Realm	User
dCloudRealm	oliver
dCloudRealm	Engineering
dCloudRealm	Administrators

DEMO:

Simplified Decryption User Interface

New Decryption UI – Key Takeaways

- **Start your journey with the Standard Decryption Policy** – intuitive, fast, and powerful
- Enjoy **90% of the capabilities** with a fraction of the setup effort – don't worry about the rule order, centrally manage exemptions (Apps, URLs, Users)
- Advanced and brown field stay with the **Rule-Based Policy for complex** conditional logic
- Convert **Standard to Rule-Based if needed** in one step

The screenshot shows the 'Standard Decryption Policy' configuration window. It has a 'Nice and easy' label and 'Cancel'/'Save' buttons. The 'Inbound Decryption' section is enabled and shows 'Source zones' (OutZone) and 'Destination zones' (InZone1). The 'Internal server details' section includes fields for 'Internal certificate object' (QUIC-Server), 'Destination network object' (QUIC-Server), and 'Destination port object' (HTTPS-UDP). The 'Outbound Decryption' section is also enabled, showing 'Source zones' (InZone1) and 'Destination zones' (OutZone). The 'Internal certificate authority' is set to 'TLS_Decrypt_SubCA'.

Standard Decryption Policy

Convert Policy Mode
(one way road)

The screenshot shows the 'Rule-based Decryption Policy' configuration window. It displays a table of rules under 'Administrator Rules' and 'Standard Rules'. The table has columns for Name, Dest Networks, Applications, Categories, SSL, and Action.

#	Name	Dest Networks	Applications	Categories	SSL	Action
Administrator Rules						
This category is empty						
Standard Rules						
1	Inbound-Decrypt-1180def02	QUIC-Server	any	any	1 Cert Status selection	Decrypt - Replace Cert
2	Block-Certificate-Status	any	any	any	3 Cert Status selections	Block with reset
3	Block-TLS-Version	any	any	any	3 Protocol Versions	Block with reset
4	Bypass-Trusted-Connections	any	any	Any (Except Uncatego	1 Client Threat selection	Do not decrypt
5	Bypass-Undecryptable-Sites (Disabled)	any	any	any	1 DN selection	Do not decrypt
6	Bypass-Apps	any	YouTube Kids, YouTube Music, YouTube TV (6 more...)	any	any	Do not decrypt
7	Bypass-Undecryptable-Apps	any	Tags: undecryptable	any	any	Do not decrypt
8	Bypass-Categories	any	any	Finance (Any reputatio, Health and Medicine (, Online Trading (Any re	any	Do not decrypt
9	Outbound-Decrypt-8fda87de48	any	any	any	any	Decrypt - Re-sign
Root Rules						
This category is empty						
Default Action						Do not decrypt

Rule-based Decryption Policy

Convert Decryption Policy to Rule-Based


Cisco Secure Firewall 10.0

QUIC Update

QUIC is no longer a niche protocol

For more stats on QUIC
check:
BRKSPM-2024

QUIC traffic evolution data 2020-2025
(Source: BRKSPM-2024)



The benefits of QUIC make it the first-choice protocol





Figure 6: Performance Comparison of QUIC and TCP for Different Application Types



Europe 2025 (Service Provider Network)

QUIC Decryption on Cisco Secure Firewall

- QUIC uses TLS 1.3 for negotiation - we follow the same decryption logic as with TLS
- QUIC is general availability in 10.0 - one click to enable

- Seamless use in the decryption policy determined by selected port object:
 - **TCP** - matches TLS connections
 - **UDP** - matches QUIC connections only
 - **Any** - matches both QUIC and TLS connections



Applies to 7.2.0 and later
☒ Enable TLS 1.3 Decryption

Applies to 7.3.0 and later
☒ Enable adaptive TLS server identity probe

Applies to 7.6.0 and later
☒ QUIC Decryption

Advanced options are available only with Snort 3


Revert to Defaults

Internal server details ?			
<input type="text" value="Search"/>			
Internal certificate object	Destination network object	Destination port object	
wildcard-example.com	Piggy-Server	HTTPS	
wildcard-example.com	File-Server	QUIC	
wildcard-example.com	App-Server	any	


QUIC Decryption Considerations

- **Inbound decryption**
 - Supported for all browsers
 - Tested servers: NGINX, NGNIXProxy, NGTCP/2, angie, aioquic, tquic, quiche, HA-Proxy, Caddy, OLS, H2O
 - Tested clients: Curl, NGTCP/2, aioquic, neqo, quiche, tquic, msquic, HA-Proxy, Caddy, OLS, H2O
- **Outbound decryption** supported on Firefox and Safari; Chromium blocks trusted CA store for certificate check in QUIC connections
- **Cluster and high availability** – decrypted session states are not synchronized – existing flows must re-establish upon switchover (same behavior as with TLS)
- **QUICv2 support planned in CY26**

Decryption Throughput*



Decryption New Conn/Sec*




* – average expected results; actual performance may vary by hardware model and traffic profile

QUIC – Key Takeaways

- **QUIC is now mainstream** (50% adoption) – performance benefits make it the first-choice protocol for modern applications – block major
- **QUIC decryption is production-ready** – General availability on Cisco Secure Firewall 10.0, same decryption principles as with TLS 1.3
- **Performance trade-off is reasonable** – 70-75% performance of TLS 1.3 decryption.
- **Inbound use-case fully supported** – protect your QUIC servers today!
- **Outbound use-case is tricky, consider 3 options:**
 - **Block QUIC traffic with AppID** – most secure and performant; may break some Apps
 - **Decrypt all outbound QUIC** – works for Firefox and Safari; triggers downgrade on Chromium; may break some apps
 - **Selective decryption + blocking with AppID** – requires ongoing monitoring and tweaking – consider blocking or excluding major contributors from your QUIC decryption policy (YouTube, Tik-Tok, Instagram, Facebook).

Encrypted Visibility Engine

What Does Encrypted Visibility Engine Provide?




Encrypted Visibility Engine Relies on TLS Fingerprints and Destination Context

TLS ClientHello

✓ Cipher Suites (18 suites)

- Cipher Suite: TLS_AES_128_GCM_SHA256 (0x1301)
- Cipher Suite: TLS_CHACHA20_POLY1305_SHA256 (0x1303)
- Cipher Suite: TLS_AES_256_GCM_SHA384 (0xc030)
- Cipher Suite: TLS_ECDHE_RSA_WITH_AES_128_GCM_SHA256 (0xc02f)
- Cipher Suite: TLS_ECDHE_RSA_WITH_AES_256_GCM_SHA384 (0xc031)
- Cipher Suite: TLS_ECDHE_RSA_WITH_CHACHA20_POLY1305_SHA256 (0xcca9)
- Cipher Suite: TLS_ECDHE_ECDSA_WITH_AES_128_GCM_SHA256 (0xc02c)
- Cipher Suite: TLS_ECDHE_ECDSA_WITH_AES_256_GCM_SHA384 (0xc032)
- Cipher Suite: TLS_ECDHE_ECDSA_WITH_CHACHA20_POLY1305_SHA256 (0xc033)
- Cipher Suite: TLS_ECDH_RSA_WITH_AES_128_GCM_SHA256 (0xc02b)
- Cipher Suite: TLS_ECDH_RSA_WITH_AES_256_GCM_SHA384 (0xc034)
- Cipher Suite: TLS_ECDH_ECDSA_WITH_AES_128_GCM_SHA256 (0xc02d)
- Cipher Suite: TLS_ECDH_ECDSA_WITH_AES_256_GCM_SHA384 (0xc035)
- Cipher Suite: TLS_ECDH_ECDSA_WITH_CHACHA20_POLY1305_SHA256 (0xc036)
- Cipher Suite: TLS_DHE_RSA_WITH_AES_128_CBC_SHA (0x0033)
- Cipher Suite: TLS_DHE_RSA_WITH_AES_256_CBC_SHA (0x0039)

TLS Fingerprint



TCP/TLS 192.168.2.110/34624->172.16.45.200/443 (SNI cisco.com)



Destination Context

Confidence: 99.94%
Process: **firefox.exe**
Version: **76.0.1**
Category: **browser**
OS: **Windows 10 19041.329**
Typical FQDN: **cisco.com**

Generate unique fingerprints for client applications based on TLS and the destination meta data

EVE evaluates a single packet in TLS/QUIC handshake – independently from decryption setup

	Time	Source	SPORT	Destination	DPORT	Protocol	Length	Info
1	0.000000	172.16.136.96	49934	18.239.83.46	443	TCP	66	49934 → 443 [SYN] Seq=0 Win=64240 Len=0 MSS=1460 WS=256 SACK_PERM
2	0.000500	18.239.83.46	443	172.16.136.96	49934	TCP	66	443 → 49934 [SYN, ACK] Seq=0 Ack=1 Win=65535 Len=0 MSS=1460 WS=64 SACK_PERM
3	0.000547	172.16.136.96	49934	18.239.83.46	443	TCP	54	49934 → 443 [ACK] Seq=1 Ack=1 Win=2097408 Len=0
4	0.000780	172.16.136.96	49934	18.239.83.46	443	TLSv1.3	585	Client Hello (SNI=www.onet.pl)
5	0.002136	18.239.83.46	443	172.16.136.96	49934	TCP	60	443 → 49934 [ACK] Seq=1 Ack=532 Win=64960 Len=0
6	0.142588	18.239.83.46	443	172.16.136.96	49934	TLSv1.3	1414	Server Hello, Change Cipher Spec, Application Data
7	0.142588	18.239.83.46	443	172.16.136.96	49934	TCP	1414	443 → 49934 [ACK] Seq=1361 Ack=532 Win=64960 Len=1360 [TCP PDU reassembled in 8]
8	0.142588	18.239.83.46	443	172.16.136.96	49934	TLSv1.3	800	Application Data, Application Data, Application Data
9	0.142630	172.16.136.96	49934	18.239.83.46	443	TCP	54	49934 → 443 [ACK] Seq=532 Ack=3467 Win=2097408 Len=0
10	0.144132	172.16.136.96	49934	18.239.83.46	443	TLSv1.3	118	Change Cipher Spec, Application Data
11	0.144272	172.16.136.96	49934	18.239.83.46	443	TLSv1.3	146	Application Data
12	0.144402	172.16.136.96	49934	18.239.83.46	443	TLSv1.3	538	Application Data
13	0.145355	18.239.83.46	443	172.16.136.96	49934	TCP	60	443 → 49934 [ACK] Seq=3467 Ack=596 Win=64896 Len=0
14	0.145433	18.239.83.46	443	172.16.136.96	49934	TCP	60	443 → 49934 [ACK] Seq=3467 Ack=688 Win=64832 Len=0
15	0.145433	18.239.83.46	443	172.16.136.96	49934	TCP	60	443 → 49934 [ACK] Seq=3467 Ack=1172 Win=64320 Len=0
16	0.156974	18.239.83.46	443	172.16.136.96	49934	TLSv1.3	304	Application Data, Application Data

QUIC looks at TLS Client Hello packet only.

Decryption disabled

Decryption enabled

How do we calculate the TLS fingerprint

Secure Firewall Application Detectors		
Field	Hex value	Human readable value
version	0303	TLS 1.2
ciphersuites	0a0a	GREASE
ciphersuites	1301	TLS_AES_128_GCM_SHA256
ciphersuites	1302	TLS_AES_256_GCM_SHA384
ciphersuites	1303	TLS_CHACHA20_POLY1305_SHA256
ciphersuites	c02b	TLS_ECDHE_ECDSA_WITH_AES_128_GCM_SHA256
ciphersuites	c02f	TLS_ECDHE_RSA_WITH_AES_128_GCM_SHA256
ciphersuites	c02c	TLS_ECDHE_ECDSA_WITH_AES_256_GCM_SHA384
ciphersuites	c030	TLS_ECDHE_RSA_WITH_AES_256_GCM_SHA384
ciphersuites	cca9	TLS_ECDHE_ECDSA_WITH_CHACHA20_POLY1305_SHA256
ciphersuites	cca8	TLS_ECDHE_RSA_WITH_CHACHA20_POLY1305_SHA256
ciphersuites	c013	TLS_ECDHE_RSA_WITH_AES_128_CBC_SHA
ciphersuites	c014	TLS_ECDHE_RSA_WITH_AES_256_CBC_SHA
ciphersuites	009c	TLS_RSA_WITH_AES_128_GCM_SHA256
ciphersuites	009d	TLS_RSA_WITH_AES_256_GCM_SHA384
ciphersuites	002f	TLS_RSA_WITH_AES_128_CBC_SHA
ciphersuites	0035	TLS_RSA_WITH_AES_256_CBC_SHA
extensions	0000	server_name
extensions	0005	status_request
	01	ocsp
extensions	000a	supported_groups
	0a0a	GREASE
		Unknown

TLS Fingerprint:

tls/1/(0303)(0a0a130113021303c02bc02fc02cc030cca9cca8c013c014009c009d002f0035)[(0000)(000500050100

(0303)

(0a0a130113021303c02bc02fc02cc030cca9cca8c013c014009c009d002f0035)

[

(0000)

(000500050100000000)

(000a000c000a0a0a11ec001d00170018)

(000b00020100)

(000d00120010040308040401)

(0010000e000c026832086874)

(0012)

(0017)

(001b0000)

(002a)

(002b)

(002c0000)

(0033)

(0a0a)

(0a0a)

(44cd)

(fe0d)

(ff01)

]

Version

Ciphers

EXTENSIONS:

server_name

status_request

supported_groups

ec_point_formats

signature_algorithms

ALPNs

signed_cert_timestamp

master_secret

rate

Billions of possible combinations

One Destination, Many Fingerprints

Destination

VDB Version

latest

Server Name

accounts.google.com

IP Address

142.250.102.84

Port

443

Firefox

TLS_AES_128_GCM_SHA256
TLS_CHACHA20_POLY1305_SHA256
TLS_AES_256_GCM_SHA384
TLS_ECDHE_ECDSA_WITH_AES_128_GCM_SHA256

supported_groups
X25519MLKEM768 (Quantum Safe)
x25519

signature_algorithms
ecdsa_sha256
ecdsa_sha384
ecdsa_sha512

compress_certificate
zlib
brtli
zstd

Chrome

TLS_AES_128_GCM_SHA256
TLS_AES_256_GCM_SHA384
TLS_CHACHA20_POLY1305_SHA256
TLS_ECDHE_ECDSA_WITH_AES_128_GCM_SHA256

supported_groups
GREASE
X25519MLKEM768 (Quantum Safe)
x25519

signature_algorithms
ecdsa_sha256
rsa_pss_sha256
rsa_sha256

compress_certificate
brtli

Preference order and the type of ciphers

Presence of GREASE (random placeholders)

Different order and count of signature algorithms

Additional certificate compressions options

... and many, many more!

Cross-launch from Unified Events Viewer
or navigate to: <https://appid.cisco.com/eve>

The Power of the Destination Context

Fingerprint

tls/1/(0303)(0a0a130113021303c02bc02fc02cc030cca9cca8c013c014009c009d002f0035)[[(

73.10% of connections with this fingerprint in EVE's database originated from the Chromium Browser

IP Address

142.250.102.84

Server Name

accounts.google.com

Port

443

Out of those 73.10% connections:


- 99.71% reached out to “accounts.google.com”
- 100% connected to 142.250.102.84
- 73.11% used port 443

	Process Name ↑ ↓	Prevalence ↑ ↓	Server Name ↑ ↓	IP Address ↑ ↓	Port ↑ ↓
☐	chromium browser	0.7310	0.9971	1.0000	0.7311
☐	slack	0.0834	0.0000	0.0000	0.0835
☐	microsoft visual studio	0.0822	0.0000	0.0000	0.0822
☐	miro	0.0281	0.0011	0.0000	0.0281
☐	figma	0.0269	0.0000	0.0000	0.0269
☐	spotify	0.0221	0.0000	0.0000	0.0221
☐	microsoft teams	0.0137	0.0000	0.0000	0.0137
☐	github desktop	0.0058	0.0000	0.0000	0.0058

The other processes (slack, miro, figma etc...) produced similar TLS fingerprints, however connected to different IPs, Domains and ports.

EVE training set enhanced with customer data

- Increased EVE accuracy:
 - **70%** more **labeled fingerprints** (processes)
 - **2 x** more **recognized OS'es**
- Training set enriched with **Cisco XDR endpoints data**
- Significant ramp up in the size of the training data set – **1 billion sessions per day** from anonymized real user flows



Encrypted Visibility Engine – Key Takeaways


- **EVE complements, not replaces decryption** – use both together for comprehensive security
- **Detects application/OS and malware activity** looking at a single TLS/QUIC packet – **minimal performance impact, no decryption required**
- **Optimise performance with Intelligent Decryption bypass** – EVE's Client Threat Score + URL Reputations
- **Continuously trained and improved on real world connections** – remember to keep VDB up-to-date
- **AppID and URL filtering for QUIC in Access Control Policy requires EVE enabled** – EVE is the decoder for QUIC Initial packets providing SNI

Shadow Traffic


Shadow Traffic Detection



Clear way to detect and monitor Shadow Traffic



Help administrators promptly react to unsanctioned connections



Combined powers of AppID, EVE and TLS/QUIC decryption.



Designed to avoid network monitoring and traffic analysis by advanced firewalls.

80+ evasive anonymizers, VPN clients, multi-hop proxies.


Hide real intention of user connectivity.

Fake TLS connections, encrypted DNS, hiding behind benign sites.

Detecting Shadow Traffic in Firewall Management Center

A new dashboard presents Shadow Traffic detected in firewall protected network divided into five categories:

- Evasive VPNs
- Encrypted DNS
- Domain Fronting
- Multi-hop Proxies
- Fake TLS



Firewall detects and flags suspicious connections showing the signs of evasion in a new column: Shadow Traffic Type.

Event Type	Action	Client Application	Web Application	Destination IP	Destination Port / ICMP Code	Shadow Traffic Type	TLS Client SNI
🔗 Connection	🟢 Allow	SSL client	XVPN	35.205.176.240	443 (https) / tcp	Evasive VPN	8v9m.com
🔗 Connection	🟢 Allow	X-VPN	Web Browsing	130.211.50.202	20005 / tcp	Evasive VPN	
🔗 Connection	🟢 Allow	X-VPN	Web Browsing	35.205.250.171	20005 / tcp	Evasive VPN	
🔗 Connection	🟢 Allow	Firefox	DNS over HTTPS	172.64.41.4	443 (https) / tcp	Encrypted DNS	mozilla.cloudflare-dns.com
🔗 Connection	🟢 Allow	Firefox	DNS over HTTPS	172.64.41.4	443 (https) / tcp	Encrypted DNS	mozilla.cloudflare-dns.com
🔗 Connection	🟢 Allow	Tor		185.220.101.192	443 (https) / tcp	Evasive VPN, Multihop Proxy	www.4vg22c3cybm7v6bqyf...
🔗 Connection	🟢 Allow	Tor		64.65.0.11	443 (https) / tcp	Evasive VPN, Multihop Proxy	www.sr33qfslszbztvrgyt3b...

DEMO:

Detecting Shadow Traffic

Five Flavors of Shadow Traffic

Shadow Traffic Connections

Evasive VPNs

30  0%

Last updated 54m ago

Multihop Proxies

10  0%

Encrypted DNS

40  0%

Domain Fronting

25  0%

Fake TLS

50  0%

Evasive VPNs

Known evasive VPN applications attempting to bypass firewall controls.

70+ VPN Apps



Monster VPN



CyberGhost

Multi-hop Proxies


Attempts to anonymize network activity.



...and more!


Encrypted DNS:

Covert domain resolution tunneling.




Domain Fronting:

HTTP header hostname and SNI/certificate mismatch – disguise true destination.



Fake TLS:

Non-standard or insecure TLS/QUIC cipher suites or domain faking.




Synergy and benefits of AppID and EVE working together

Detection engine	Evasive VPNs	Multi-hop Proxy	Encrypted DNS	Domain Fronting	Fake TLS
EVE	✓	✓	✓	✗	✓
AppID	✓	✓	✓	✓ *	✗

Shadow traffic detection leverage both **machine learning** and traditional **signature-based** engines:

- EVE extends visibility into encrypted traffic identifying client processes and source OS
- AppID provides granular application detection with deep inspection in unencrypted or decrypted traffic.
- Domain Fronting (*) requires TLS/QUIC decryption to compare TLS endpoint with the real HTTP request

Domain Fronting – Hide Behind Legitimate TLS Connection




DEMO:

Domain Fronting

Encrypted DNS Challenges

- The web browser bypasses OS DNS stack
- Avoids DNS based corporate security controls and logging
- Delegates DNS control to a content provider (e.g. Cloudflare)




Shadow Traffic – Key Takeaways

- **EVE + AppID + Decryption working together** to detect 80+ evasive tools, domain fronting and fake TLS
- **Evasive tools evolve constantly** – configure restrictive policy with and monitor closely for Shadow Traffic (assume something sneaks out sooner or later)
- **Enable EVE and Shadow Traffic detection** – review regularly and identify endpoints/users attempting to bypass your controls
- **Educate your users** and ensure your organization’s **Security Policy sanctions use of evasive software**
- **Do not block “DNS Crypt” if you use Umbrella** – this AppID matches Cisco Umbrella services

Encrypted Client Hello

Firewall enforcement heavily relies on this single TLS extension


	Time	Source	SPORT	Destination	DPORT	Protocol	Length	Info
1	0.000000	172.16.136.96	49934	18.239.83.46	443	TCP	66	49934 → 443 [SYN] Seq=0 Win=64240 Len=0 MSS=1460
2	0.000500	18.239.83.46	443	172.16.136.96	49934	TCP	66	443 → 49934 [SYN, ACK] Seq=0 Ack=1 Win=65535 Len=
3	0.000547	172.16.136.96	49934	18.239.83.46	443	TCP	54	49934 → 443 [ACK] Seq=1 Ack=1 Win=2097408 Len=0
4	0.000780	172.16.136.96	49934	18.239.83.46	443	TLSv1.3	585	Client Hello (SNI=www.onet.pl)




What is Encrypted Client Hello (ECH)?

Learn more: RSAC 2025 “ECH: Hello to Enhanced Privacy or Goodbye to Visibility?”


- ECH is the last piece of the puzzle to close SNI security gap – HPKE, Encrypted DNS, service bindings for DNS ... and more!
- You can still recognize the Service Provider hosting the real destination – e.g. Clourflare, Akamai, Fastly etc...
- ECH requires bootstrap configuration from the Service Provider




Why should we care?



of **browsers**
support ECH¹



Of top **1M sites**
have ECH enabled²



Of top **10K sites**
have ECH enabled³

- The **ECH infrastructure is ready and fully operational** on both the user (browsers) and the CDN side.
- Most web browsers support ECH and actively send **fake ECH extensions to GREASE the Internet**.
- Cloudflare is the first CDN to **fully support Encrypted Client Hello** and the destination for almost all ECH traffic
- ECH is at its final draft 25 - expected to be ratified **any day now...**

Prepare for :


- Impairment of existing network-centric security stack – firewall, IPS, etc...
- Malware, C2, exfiltration (etc...) hiding under the radar

¹ - <https://www.stetic.com/market-share/browser/>

² - <https://portal.onersac.com/library/B00507DF8D944ED79CA2D5EA1FD168E8>

³ - <https://divested.dev/misc/ech.txt>

The “nightmare” crypto stack is here...



...and you can set it up in three simple steps...

1. Register a domain.



YOUR DOMAINS [1/1]					
No.	Domain	Registered at	Expires	Days left	Actions
1	☐ pig-in-the-middle.pl	2025-07-23 18:31:11	2026-07-23 18:31:11	316	Details Host Advertise

2. Set up your web server.

```
server {  
    listen 443 quic reuseport;  
    listen 443 default_server ssl;  
    http2 on; http3 on; http3_hq on;  
    server_name pig-in-the-middle.pl;  
    quic_retry on;  
    ssl_early_data on;  
    ssl_certificate /etc/letsencrypt/fullchain.pem;  
    ssl_certificate_key /etc/letsencrypt/privkey.pem;  
}
```



3. Sign-up for a free plan*
at Cloudflare and
delegate your domain.



Domain	Status ⓘ	Security insights ⓘ	Unique visitors ⓘ	Plan
pig-in-the-middle.pl	✓ <u>Active</u>	Enable	 151	Free

* - ECH cannot be disabled in Cloudflare's free plan – potentially hiding thousands of web pages behind **cloudflare-ech.com**.

...et voila!

QUIC Protocol – Certificate Pinned

No.	Time	Source	SPORT	Destination	DPORT	Protocol	Length	Info
196	05:00:02.478506	2a01:110f:4404:3400:451d:2176:7833:79a2	54251	2a06:98c1:52::4	443	QUIC	1294	Initial, DCID=51caa96f95cefdf1da9f0982, SCID=92f450, PKN: 1, CRYPTO
1673	05:00:06.014693	2a01:110f:4404:3400:451d:2176:7833:79a2	54258	2606:4700:3030::6815:1001	443	QUIC	1294	Initial, DCID=a658f1d5031e05a9, SCID=35bab5, PKN: 1, CRYPTO

TLsv1.3 Record Layer: Handshake Protocol: Client Hello

Handshake Protocol: Client Hello

Handshake Type: Client Hello (1)

Length: 1788

Version: TLS 1.2 (0x0303)

> [Expert Info (Chat/Deprecated): This legacy_version field MUST be ignored. The supported_versions extension is present and MUST be used instead.]

Random: 81eb04265af6f7eb56550f9feb0ad2418fd6a28b59a929d9dc4db01bae6b49aa

Session ID Length: 0

Cipher Suites Length: 6

> Cipher Suites (3 suites)

Compression Methods Length: 1

> Compression Methods (1 method)

Extensions Length: 1741

> Extension: key_share (len=132)

> Extension: psk_key_exchange_modes (len=2)

> Extension: delegated_credentials (len=10)

> Extension: extended_master_secret (len=0)

> Extension: record_size_limit (len=2)

> Extension: supported_versions (len=3) TLS 1.3

> Extension: signature_algorithms (len=24)

> Extension: application_layer_protocol_negotiation (len=5)

> Extension: server_name (len=23) name=cloudflare-ech.com

> Extension: supported_groups (len=12)

> Extension: renegotiation_info (len=1)

> Extension: status_request (len=5)

> Extension: quic_transport_parameters (len=33)

> Extension: encrypted_client_hello (len=249)

Encrypted

DNS

PQC Keyshare

ECH


ECH

Nothing here ☹️

Date/Time	Event Type	Initiator IP	Responder IP	Responder Port	Action	Application	Client Application	Initiator Port	URL	Web Application
Sep 5, 2025, 05:02:12	Connect...	2a01:110f:...	2a06:98c1:...	443	Allow	QUIC	QUIC client	54251		Unknown
Sep 5, 2025, 05:02:12	Connect...	2a01:110f:...	2606:4700:...	443	Allow	QUIC	QUIC client	54258		Unknown

Encrypted Client Hello Step-by-Step

-  - ECH private key
-  - ECH public key
-  - HPKE protected ECH payload



DEMO:

Observing the ECH connection in Wireshark

Can a firewall block ECH connections?

Can you tell which of the below is FAKE?

Extensions Length: 1723

```
> Extension: server_name (len=23) name=cloudflare-ech.com
> Extension: extended_master_secret (len=0)
> Extension: renegotiation_info (len=1)
> Extension: supported_groups (len=16)
> Extension: ec_point_formats (len=2)
> Extension: session_ticket (len=0)
> Extension: application_layer_protocol_negotiation (len=14)
> Extension: status_request (len=5)
> Extension: delegated_credentials (len=10)
> Extension: signed_certificate_timestamp (len=0)
> Extension: key_share (len=1327) X25519MLKEM768, x25519, secp256r1
> Extension: supported_versions (len=5) TLS 1.3, TLS 1.2
> Extension: signature_algorithms (len=24)
> Extension: psk_key_exchange_modes (len=2)
> Extension: record_size_limit (len=2)
> Extension: compress_certificate (len=7)
✓ Extension: encrypted_client_hello (len=217)
  Type: encrypted_client_hello (65037)
  Length: 217
  Client Hello type: Outer Client Hello (0)
  > Cipher Suite: HKDF-SHA256/AES-128-GCM
  Config Id: 78
  Enc length: 32
  Enc: 458b46b4eac77be5f27d88f2e05024ae05ba24ff9d5c189c6bf028bc05944c69
  Payload length: 175
  Payload [...]: 535cb048d6fa2d98f38cc05bc471dbd3f84b144a40645d7ee3eada580e3
  JA4: t13d17/17h2_5b57614c22b0_3cbfd9057e0d1
```

Extensions Length: 1780

```
> Extension: server_name (len=12) name=onet.pl
> Extension: extended_master_secret (len=0)
> Extension: renegotiation_info (len=1)
> Extension: supported_groups (len=16)
> Extension: ec_point_formats (len=2)
> Extension: session_ticket (len=0)
> Extension: application_layer_protocol_negotiation (len=14)
> Extension: status_request (len=5)
> Extension: delegated_credentials (len=10)
> Extension: signed_certificate_timestamp (len=0)
> Extension: key_share (len=1327) X25519MLKEM768, x25519, secp256r1
> Extension: supported_versions (len=9) TLS 1.3, TLS 1.2, TLS 1.1, TLS 1.0
> Extension: signature_algorithms (len=24)
> Extension: psk_key_exchange_modes (len=2)
> Extension: record_size_limit (len=2)
> Extension: compress_certificate (len=7)
✓ Extension: encrypted_client_hello (len=281)
  Type: encrypted_client_hello (65037)
  Length: 281
  Client Hello type: Outer Client Hello (0)
  > Cipher Suite: HKDF-SHA256/AES-128-GCM
  Config Id: 193
  Enc length: 32
  Enc: 2fcf7e2477f10f36ce71dd5bacdc4b74a8a7ab9615ae4187898194e12f8c6c1b
  Payload length: 239
  Payload [...]: 499220070ad114ced1320175e9b924ba656d0b67d233b2d393295d915e68a8
  JA4: t13d181/h2_e8a523a4129/3cbfd9057e0d1
```

Can a firewall figure out if server accepted ECH?

Server's acceptance of ECH proposal encoded in the last 8 bytes of Random value...

Real ECH - Server Hello

Transport Layer Security	
▼ TLSv1.3 Record Layer: Handshake Protocol: Server Hello	
Content Type: Handshake (22)	
Version: TLS 1.2 (0x0303)	
Length: 1210	
▼ Handshake Protocol: Server Hello	
Handshake Type: Server Hello (2)	
Length: 1206	
> Version: TLS 1.2 (0x0303)	
Random: 5164dec3639e45dbbb1e2ad875b6c56c8f652f3003348a57bd627f7136f77b3	
Session ID Length: 32	
Session ID: c38222699a03fb7e17659e1c95264e9fbdab19c4131a2a0a546ccb9d4b0af626	
Cipher Suite: TLS_AES_128_GCM_SHA256 (0x1301)	
Compression Method: null (0)	
Extensions Length: 1134	
> Extension: key_share (len=1124) X25519MLKEM768	
> Extension: supported_versions (len=2) TLS 1.3	

Fake ECH - Server Hello

Transport Layer Security	
▼ TLSv1.3 Record Layer: Handshake Protocol: Server Hello	
Content Type: Handshake (22)	
Version: TLS 1.2 (0x0303)	
Length: 1210	
▼ Handshake Protocol: Server Hello	
Handshake Type: Server Hello (2)	
Length: 1206	
> Version: TLS 1.2 (0x0303)	
Random: 4e347c055d50c51dcfe89fde91e218e48226fb7ce41c73d75b6b05e58ed9648	
Session ID Length: 32	
Session ID: 4d7cec89f7e13c3f1b3790b278cc414a610265547111d63128dc267ca1983cab	
Cipher Suite: TLS_AES_128_GCM_SHA256 (0x1301)	
Compression Method: null (0)	
Extensions Length: 1134	
> Extension: supported_versions (len=2) TLS 1.3	
> Extension: key_share (len=1124) X25519MLKEM768	

The server response does not explicitly acknowledge acceptance of ECH by the standard
(this prevents Middleboxes from detecting real attempt)

Can we block packets to known ECH servers (e.g. cloudflare-ech.com)?

Source	SPORT	Destination	DPORT	Protocol	Length	Info
2a01:110f::b4e0	58768	2a06:98c1:52::4	443	TLSv1.3	752	Client Hello (SNI=mozilla.cloudflare-dns.com)
2a01:110f::b4e0	58789	2606:4700:3030::6815:4001	443	TLSv1.2	553	Client Hello (SNI=cloudflare-ech.com)
2a01:110f::b4e0	58790	2606:4700:3030::6815:4001	443	TLSv1.2	553	Client Hello (SNI=cloudflare-ech.com)
2a01:110f::b4e0	58792	2606:4700:3030::6815:4001	443	TLSv1.2	553	Client Hello (SNI=cloudflare-ech.com)
2a01:110f::b4e0	58348	2606:4700:3030::6815:4001	443	TLSv1.2	680	Client Hello (SNI=cloudflare-ech.com)
2a01:110f::b4e0	58655	2606:4700:3030::6815:6001	443	TLSv1.2	680	Client Hello (SNI=cloudflare-ech.com)
2a01:110f::b4e0	58660	2606:4700:3030::6815:7001	443	TLSv1.2	680	Client Hello (SNI=cloudflare-ech.com)
2a01:110f::b4e0	58662	2606:4700:3030::6815:3001	443	TLSv1.2	680	Client Hello (SNI=cloudflare-ech.com)
2a01:110f::b4e0	58664	2606:4700:3030::6815:5001	443	TLSv1.3	746	Client Hello (SNI=pig-in-the-middle.pl)

DNS over HTTPs query

Connection attempts to the ECH client facing servers timing-out (15 seconds each)


Fallback to clear-text SNI after 120 seconds...

“This technology is a way to bypass restrictions on access to information that’s banned in Russia. Using it goes against Russian law.” – Roskomnadzor (Russia’s media censor) after it blocked thousands of websites using ECH (November 2024)

Three lines of defenses against ECH

1. Strict control over DNS – prevent the client from learning ECH configuration

- Configure your DNS to scrub ECH config or block the whole HTTPS record
- Block the "canary domain" use-application-dns.net – to let know the browsers they can't use DoX
- Block encrypted DNS in the firewall policy
- Block unauthorised DNS servers



2. Disable ECH/encrypted DNS on managed endpoints (e.g. Firefox/Chrome policy-templates):


- DisableEncryptedClientHello (does not stop fake ECH)
- DNSoverHTTPS Locked

Use secure DNS

Make it harder for people with access to your Internet traffic to see which sites you visit. Chrome uses a secure connection to look up a site's IP address in the DNS (Domain Name System).




3. Reduce ECH traffic as much as possible (with above) and consider TLS/QUIC decryption to downgrade ECH.



Downgrade ECH with trusted Key-Resign Decryption

With the current backoff logic (tested on latest Firefox and Chrome), decrypting connections towards ECH Client Facing Servers gracefully downgrades the connection to clear text SNI.



As per the ECH draft 25 when a middlebox acts as TLS proxy ignoring ECH:

- Depending on whether the **client is configured to accept the proxy's certificate as authoritative for the public name**, this may trigger the retry logic. [8.2]
- [...] **the client can regard ECH as securely disabled by the server**, and it **SHOULD** retry the handshake with a new transport connection and ECH disabled. [6.1.6]

DEMO:

**Downgrade ECH with
decryption**

Encrypted Visibility Engine to the rescue?

Event Type	Action	Destination IP	URL	Web Application	Encrypted Visibility Process Name	Encrypted Visibility Process Confidence Score	Encrypted Visibility Fingerprint
↪ Connection	➔ Allow	172.67.135.44	https://cloudflare-ech.com	ECH Servers	chromium browser	98%	🔒 quic/(00000001)(0303)(130113021303

...but the destination is hidden by ECH
(https://pig-in-the-middle.pl)

EVE tells us the connection was
initiated by Chrome...

The true **destination remains unknown**, but **EVE provides a strong indication** something suspicious is going on:

Time	Event Type	Action	Source IP	Web Application	Destination IP	Destination Port / ICMP Code	URL	Encrypted Visibility Process Name	Encrypted Visibility Proces...
> 2025-10-30 14:39:01	↪ Connection	➔ Allow	198.19.10.103	ECH Servers	104.18.11.118	443 (https) / tcp	https://cloudflare-ech.com	generic dmz process	65%
> 2025-10-30 14:36:46	↪ Connection	➔ Allow	198.19.10.103	ECH Servers	104.18.10.118	443 (https) / tcp	https://cloudflare-ech.com	rancher desktop	100%
> 2025-10-30 14:36:30	↪ Connection	➔ Allow	198.19.10.21	ECH Servers	172.67.135.44	443 (https) / udp	https://cloudflare-ech.com	chromium browser	98%
> 2025-10-30 14:36:20	↪ Connection	➔ Allow	198.19.10.21	ECH Servers	104.21.26.24	443 (https) / tcp	https://cloudflare-ech.com	firefox browser	100%

ECH traffic originating from a non-standard browser
can be a sign of something fishy.



In early 2024, while analysing targeted attacks [...] we identified a noteworthy piece of malware[...] distinguishing itself by leveraging Encrypted Client Hello (ECH) for its C&C communications [...] significantly harder to detect and block using conventional security products.

Yuta Sawabe & Rintaro Koike (NTT Security Holdings)

<https://www.virusbulletin.com/conference/vb2025/abstracts/stealth-over-tls-emergence-ech-based-cc-echidna-malware/>

Encrypted Client Hello - Key Takeaways

- **Implement DNS control NOW** – prevent ECH bootstrap before it happens
- **ECH hides SNI and breaks most of the NGFW stuff** – URL filtering, TLS probing, selective decryption...
- 59% of browsers and 10% of top 1M sites support **ECH - infrastructure is ready, and adoption is accelerating rapidly**
- Three-layer defense: (1) **Strict DNS Control**, (2) **Endpoint Policies**, (3) **Selective Decryption and Blocking**
- **Monitor for EVE-detected unusual processes** connecting to known ECH Servers (e.g. malware using CnC hosted behind CDNs)

Certificate Management

The “CA/Browser Forum Mob” says...



- *“Your life ain’t gonna be too long, pal.”*

Certificate Lifetime Shortens By Half Every 2 Years

The **CA/Browser Forum** – an alliance of browser and public CA vendors – holding the power to decide how long certificates can live on the public web.

✚ Frequent certificate rotation = faster adoption of stronger keys & algorithms, reduce stale ownership and security exposure

■ Higher operational frequency, automation becomes essential, little tolerance to missed renewals...

From
degree-length
lifetime...



...to milk expiry



When the “milk” gets sour, it brings down the Giants...

EXPIRED AUTHENTICATION CERTIFICATE

Microsoft Teams knocked offline by expired authentication certificate – a three-hour global outage of Microsoft Teams, leaving over **20 million users** unable to log in or send messages.

[3 February 2019]

EXPIRED SIP SERVER CERTIFICATE

Google Voice suffered a four-hour outage after SIP servers failed certificate validation. During the incident, **users could not initiate or receive VoIP calls**, impacting business communications across multiple regions.

[15–16 February 2021]

EXPIRED GROUD-STATIONS CERTIFICATE

SpaceX Starlink suffers downtime from expired ground station certificate – an expired digital certificate on SpaceX’s ground control systems triggered a **global connectivity loss** for Starlink users lasting several hours.

[8 April 2023]

EXPIRED ROOT CA CERTIFICATE


A root certificate expiration caused **Cisco SD-WAN** endpoints worldwide to lose registration with Secure Access (Umbrella DNS). The issue **disrupted network connectivity** until new trust anchors were deployed.

[30 September 2024]

Building a process so your milk never gets that ‘extra flavour’




Server Certificate Lifecycle Management




Automatically obtain, renew and deploy certificates using ACME, off-shelf CLM* or custom orchestration workflows.

Flexible Certificate Usage on the Firewall



Scale decryption configuration easily and enable seamless, zero-downtime certificate rotation.

Firewall Update API



Automate certificate provisioning and updates with an intuitive programmatic interface.

* - Certificate Lifecycle Management

An RFC Standard to the Rescue – Automated Certificate Management Environment (ACME)



ACME is an open RFC8555 standard protocol that automates the **issuance**, **validation**, and **renewal** of digital certificates – eliminating the need for manual, error-prone steps.


Key benefits:

- Streamlines certificate deployment and renewal
- Ensures continuous trust without human intervention
- Integrates easily with automation tools, CLM systems, and firewalls

Domain validation methods:

- **HTTP-01 Challenge** – Proves domain control via an HTTP resource
- **DNS-01 Challenge** – Proves control by creating a specific DNS record
- **TLS-ALPN-01 Challenge** – Validates ownership through a custom TLS handshake

Automatic Certificate Management Environment (ACME)




DEMO:

Automating Certificate Lifecycle with ACME and Certbot


Certificate Replace – Flexible Certificate Design

New in
FTD 10.0




Certificate Replace – New Known-Key Decryption Method

Single SAN Certificate Replace




Certificate Replace – New Known-Key Decryption Method

Multi-SAN Certificate Replace




Certificate Replace – New Known-Key Decryption Method

Wildcard Certificate Replace



Automatic Certificate Management Environment (ACME)



Streamline Certificate Updates – User Interface and REST

- Update an existing object with a new certificate
- Decryption Policy remains unchanged
- Update certificate object and re-deploy
- Available in FMC UI and via REST API:

GET	/api/fmc_config/v1/domain/{domainUUID}/object/internalcertificates
POST	/api/fmc_config/v1/domain/{domainUUID}/object/internalcertificates
DELETE	/api/fmc_config/v1/domain/{domainUUID}/object/internalcertificates/{objectId}
GET	/api/fmc_config/v1/domain/{domainUUID}/object/internalcertificates/{objectId}
PUT	/api/fmc_config/v1/domain/{domainUUID}/object/internalcertificates/{objectId}

The image shows two screenshots from the Cisco FMC UI. The background screenshot is the 'Edit Internal Certificate' form, which includes fields for Name, Subject, Issuer, Not Valid Before, Not Valid After, and Serial Number. The 'Update certificate' button at the bottom is highlighted with a pink box. A red arrow points from this button to a foreground screenshot of the 'Update Internal Certificate' modal. This modal contains fields for Name, Certificate Data (with a 'Browse..' button), Key (with a 'Browse..' button), and an 'Encrypted, and the password is:' checkbox with a password field. 'Cancel' and 'Save' buttons are at the bottom right of the modal.



DEMO:

Certificate Update with REST API

Certificate Management – Key Takeaways

- When certificate lifetime drops to 47 days by 2029 – **manual renewal is unsustainable**
- Simplify with certificate replace – 1 wildcard certificate = decrypt entire domain (*.example.com) – backend certificates are not exposed to the end users
- **Implement ACME or other Certificate Lifecycle Management (CLM) solutions NOW** – don't wait for the first outage
- Manual certificate renewal takes around **45 minutes vs. 30 seconds** with CLM-powered automation* – multiply by hundreds of certificates...

Post Quantum Cryptography

What's the big deal about Quantum Computing?

Quantum computing:

- Is a fundamentally new model of computation
- Enables an **exponential speed-up** for specific mathematical problems


The impact:

- Poses a serious **long-term threat** to **data confidentiality**
 - “Harvest now, decrypt later” – becomes a real concern
- **Cryptographically relevant** quantum computers expected within **5-15 years**
- Breaking today's encryption will be **extremely costly** – **but feasible** for well-funded actors
- Anticipate **targeted attacks** on the **highest value data**:
 - state secrets, intellectual property, executive communications




That is still sometime in the future... but inevitable...

How does quantum computing affect TLS security?



The Impact on Asymmetric and Symmetric Cryptography


Peter Shor



Algorithm	Based On	Classical Computer Time	Shor's Algorithm Time on Quantum Computer (Future)
RSA-3072	Integer Factorization	$\sim 10^{25}$ years	Hours -> Weeks
ECC-256	Elliptic Curve Log	$\sim 10^{38}$ years	Hours -> Days

! We need a new Quantum-Resistant public key algorithm.

Lov Grover




AES Key Size	Grover's Effective Attack (Brute-Force)	Effective Key Strength
AES-128	$\sim 2^{64}$ operations	Equivalent to 64-bit key
AES-256	$\sim 2^{128}$ operations	Equivalent to 128-bit key


i Doubling symmetric key size provides Quantum-Safety.

How Much Traffic on The Internet is Quantum Safe?

- ML-KEM requires server-side and client-side support




of top 1M sites support PQC*



of browser requests propose PQC*

Post-Quantum Protected HTTPs Traffic (at Cloudflare)



Source: Cloudflare Signals Report 2025

- **Client-side support:**
 - Firefox 132+(Oct/2024)
 - Chrome/Edge 131+ (Nov 2024)
 - Safari 26+ (Sep/25)

Module-Lattice Key-Encapsulation Mechanism (ML-KEM) – post-quantum key encapsulation mechanism based on **mathematical problem designed to resist quantum attacks.**

*Source: <https://www.f5.com/labs/articles/the-state-of-pqc-on-the-web> (data from June/25)

How to check if my connection is Quantum Safe?

```

Handshake Protocol: Client Hello
Handshake Type: Client Hello (1)
Length: 2230
> Version: TLS 1.2 (0x0303)
Random: 194fdb670d9ed68f2c3f99b3dfb9b86f9a1c020d3c6387b4162009601c9e66c6
Session ID Length: 32
Session ID: 3e7a5a970e829a65021eb5e5b05f4f1755667cbbbbb39bce307b4052abe25ac
Cipher Suites Length: 32
> Cipher Suites (16 suites)
> Extension: supported_versions (len=7) TLS 1.3, TLS 1.2
> Extension: ec_point_formats (len=2)
> Extension: supported_groups (len=12)
> Extension: signature_algorithms (len=18)
> Extension: compress_certificate (len=3)
> Extension: encrypted_client_hello (len=218)
> Extension: key_share (len=1263) X25519MLKEM768, x25519
  Type: key_share (51)
  Length: 1263
  > Key Share extension
    Client Key Share Length: 1261
    > Key Share Entry: Group: Reserved (GREASE), Key Exchange length: 1
    > Key Share Entry: Group: X25519MLKEM768, Key Exchange length: 1216
    > Key Share Entry: Group: x25519, Key Exchange length: 32
  > Extension: server_name (len=19) name=www.google.com

```

Client Hello



Client

```

Handshake Protocol: Server Hello
Handshake Type: Server Hello (2)
Length: 1212
> Version: TLS 1.2 (0x0303)
Cipher Suite: TLS_AES_128_GCM_SHA256 (0x1301)
Compression Method: null (0)
Extensions Length: 1140
> Extension: pre_shared_key (len=2)
> Extension: key_share (len=1124) X25519MLKEM768
  Type: key_share (51)
  Length: 1124
  > Key Share extension
    > Key Share Entry: Group: X25519MLKEM768, Key Exchange length: 1120
  > Extension: supported_versions (len=2) TLS 1.3

```

Server Hello



Server

Quantum Resistant Key Exchange Through a Firewall

→ X25519-ML-KEM768
→ X25519

Inspect Only

X25519-ML-KEM768
negotiated



Client

Firewall



Server

Choose the
strongest.

Inspect & Decrypt

X25519 negotiated



Client

Firewall



Server

Strip unsupported
Key Exchange.

The client
doesn't
support PQC.

Post-Quantum Cryptography – Key Takeaways

- Quantum computers will break RSA/ECC within 5-15 years – **"harvest now, decrypt later" is real.**
- Put yourself in the attacker's shoes: **What encrypted data in YOUR network is worth paying to store for a decade, waiting for quantum computers to crack it open?**
- **Enable TLS 1.3 everywhere to support hybrid PQC key exchange** – 57% of browsers already propose ML-KEM768
- Hardware refresh cycles: **ensure new security infrastructure purchases include PQC support** – retrofitting is expensive
- Consider PQC downgrade when firewall decrypts for inspection – **Cisco Secure Firewall will support ML-KEM768 in CY26**

Conclusions

Your Action Plan – Priority Matrix

IMMEDIATE (Next 30 days)

- Enable EVE and update to VDB including ECH Servers AppID
- Audit encrypted DNS settings – implement strict DNS control
- Review certificate inventory – identify manual renewal risks
- Baseline QUIC and ECH traffic in you network

SHORT-TERM (Next 90 days)

- Evaluate ACME/CLM solution for certificate automation
- Implement selective TLS/QUIC decryption for critical traffic
- Test ECH downgrade for known CDN servers
- When on 10.0 enable Shadow Traffic detection on all FTD devices
- Review PQC readiness (TLS 1.3 everywhere)

STRATEGIC (Next 6-12 Months)

- Design security stack assuming zero clear-text visibility
- Prepare for post-quantum cryptography migration – watch out for software updates
- Train security teams on encrypted visibility techniques

Please share your **feedback and ideas**

Before leaving the room, please share your feedback on this session!



- It is very important for me **personally** and ...
- ... your comments, feedback and ideas provide **the most valuable input** for our engineering

Complete your session evaluations



Complete a minimum of 4 session surveys and the Overall Event Survey to claim a Cisco Live T-Shirt.



Earn up to 800 points by completing all surveys and climb the Cisco Live Challenge leaderboard.



Level up and earn exclusive prizes!



Complete your surveys in the Cisco Live Events app.

Continue your education



Visit the Cisco Stand for related demos



Book your one-on-one Meet the Expert meeting



Attend the interactive education with Capture the Flag, and Walk-in Labs



Visit the On-Demand Library for more sessions at www.CiscoLive.com/on-demand

Contact me at: cgrabows@cisco.com

Thank you

CISCO Live !

